REFERRAL FOR PROPOSED ACTION

RANGER 3 DEEPS UNDERGROUND MINE

FIGURES 1 – 20

LIST OF FIGURES

Figure 1: Location of the Ranger Project Area 1

Figure 2: Contextual overview of the Ranger 3 Deeps mineral resource and indicative footprint of key infrastructure within the Ranger Project Area, including matters of national environmental significance (MNES) search co-ordinates. See Figure 11 for an enlargement of the immediate area of the proposed action. (NB: stockpiles, pond and portal are existing infrastructure constructed for the Ranger 3 Deeps Exploration Decline project.) 2

Figure 3: Indicative location of the proposed action infrastructure in relation to existing infrastructure 3

Figure 4: Provisional layout: Potential mining areas, plan view showing the extent of mineralisation relative to Pit 3 4

Figure 5: Schematic cross-section through the Ranger 3 Deeps area 5

Figure 6: Geology block model – small block Ordinary Kriging (OK) – 10 m x 10 m x 5 m block size 5

Figure 7: Cross section of stoping layout 6

Figure 8: Generic arrangement of drives, cross-cuts, stope development and ventilation system. The orebody slopes from the top left to the bottom right. All drives and the vent shaft are constructed prior to the cross-cuts into the mineralised material. 6

Figure 9a: Stoping – blast hole drilling of cut-off slot (stope dimensions: width of ore body 20 to 40 m x 25 m high x 20 m along strike) 7

Figure 9b: Cut-off is blasted and loaded out 7

Figure 10: Paste backfilling 8

Figure 11: Ranger 3 Deeps (including primary infrastructure) relative to the location of the R34 cultural heritage site 8

Figure 12: Noise and vibration modelling nearest sensitive receptors 9

Figure 13: Cumulative noise levels from existing operations and the proposed action, relative to New South Wales industrial noise criteria 10

Figure 14: Relationship between distance, blast source and resultant vibration. (Note: all development for the proposed action is at a depth of greater than 300 m and the nearest sensitive receptor is approximately 2 km from the blast point.) 10

Figure 15: Typical surface backfill plant 11

Figure 16: Generic paste backfill flowsheet 11

Figure 17: Schematic showing concept of "raise bore" ventilation shaft construction 12

Figure 18: Vent raise schematic 12

Figure 19: Existing processing circuit showing the pathway for beneficiated ore to enter the circuit 13

Figure 20: Ranger production forecast to 2020, in the absence of the proposed action 14



Figure 1: Location of the Ranger Project Area



Figure 2: Contextual overview of the Ranger 3 Deeps mineral resource and indicative footprint of key infrastructure within the Ranger Project Area, including matters of national environmental significance (MNES) search co-ordinates. See Figure 11 for an enlargement of the immediate area of the proposed action. (NB: stockpiles, pond and portal are existing infrastructure constructed for the Ranger 3 Deeps Exploration Decline project.)

Figure 3: Indicative location of the proposed action infrastructure in relation to existing infrastructure



Figure 4: Provisional layout: Potential mining areas, plan view showing the extent of mineralisation relative to Pit 3



Figure 5: Schematic cross-section through the Ranger 3 Deeps area



Figure 6: Geology block model – small block Ordinary Kriging (OK) – 10 m x 10 m x 5 m block size



Figure 7: Cross section of stoping layout



Figure 8: Generic arrangement of drives, cross-cuts, stope development and ventilation system. The orebody slopes from the top left to the bottom right. All drives and the vent shaft are constructed prior to the cross-cuts into the mineralised material.



Figure 9a: Stoping – blast hole drilling of cut-off slot (stope dimensions: width of ore body 20 to 40 m x 25 m high x 20 m along strike)



Figure 9b: Cut-off is blasted and loaded out



Figure 10: Paste backfilling



Figure 11: Ranger 3 Deeps (including primary infrastructure) relative to the location of the R34 cultural heritage site

Figure 12: Noise and vibration modelling nearest sensitive receptors



Figure 13: Cumulative noise levels from existing operations and the proposed action, relative to New South Wales industrial noise criteria



Figure 14: Relationship between distance, blast source and resultant vibration. (Note: all development for the proposed action is at a depth of greater than 300 m and the nearest sensitive receptor is approximately 2 km from the blast point.)

Figure 15: Typical surface backfill plant



Figure 16: Generic paste backfill flowsheet



Figure 17: Schematic showing concept of "raise bore" ventilation shaft construction



Figure 18: Vent raise schematic



Figure 19: Existing processing circuit showing the pathway for beneficiated ore to enter the circuit



Figure 20: Ranger production forecast to 2020, in the absence of the proposed action