



**Rustlers Roost and Quest 29  
Open-Cut Mine Redevelopment**

**Draft Environmental Impact  
Statement (EIS)**

**Section 7.3 - Hydrological  
Processes**

*Prepared pursuant to the Environment Protection Act 2019*

October 2021

# Table of Contents

<b>Acronyms, Abbreviations and Units .....</b>	<b>xvii</b>
<b>Section 1 Introduction .....</b>	<b>1</b>
1.1 Overview .....	1
1.2 Key Objectives .....	2
1.3 Location and Regional Setting .....	3
1.4 Proponent Details .....	6
1.4.1 Contact Details .....	6
1.4.2 Organisational Structure .....	6
1.4.3 Environmental Record .....	7
1.5 Land Tenure and Zoning .....	8
1.6 Proposal Background and Proposed Changes .....	13
1.6.1 Current Land Use .....	13
1.6.2 Historic Land Use .....	13
1.6.3 Proposed Changes .....	19
1.7 Project Benefits .....	21
1.8 Draft EIS Structure .....	22
1.9 Cross-Reference .....	23
1.10 Changes Since Project Referral .....	27
<b>Section 2 Regulatory Context .....</b>	<b>33</b>
2.1 Commonwealth .....	33
2.1.1 Environment Protection and Biodiversity Conservation Act 1999 .....	33
2.1.2 Native Title Act 1993 .....	34
2.2 Northern Territory .....	34
2.2.1 Environment Protection Act 2019 .....	34
2.2.2 Mining Management Act 2001 .....	35
2.2.3 Mineral Titles Act 2010 .....	36
2.2.4 Territory Parks and Wildlife Conservation Act 2000 .....	36
2.2.5 Other Northern Territory Legislation .....	36
2.3 Relevant Agreements .....	38
<b>Section 3 Stakeholder Engagement .....</b>	<b>39</b>
3.1 Engagement Purpose, Objectives and Outcomes .....	39
3.1.1 Purpose and Objectives .....	39
3.1.2 Outcomes .....	40
3.2 Stakeholder Engagement Strategy .....	40
3.2.1 Overview of Approach .....	40
3.2.2 Principles for Project Engagement .....	40
3.2.3 Significant Variation Process .....	41
3.3 Stakeholder Analysis .....	42
3.3.1 IAP2 Core Values .....	42

# Table of Contents

---

3.3.2	Key Stakeholders .....	43
3.4	Level of Engagement .....	44
3.5	Identification of Potential Concerns and Opportunities .....	45
3.6	Level of Engagement and Activities .....	46
3.7	Stakeholder Engagement to Date .....	49
3.8	Future Engagement.....	52
<b>Section 4 Project Description .....</b>		<b>55</b>
4.1	Overview .....	55
4.2	Resource Details.....	59
4.3	Existing Disturbance and Proposed Footprint.....	61
4.3.1	Existing Disturbance Footprint .....	61
4.3.2	Proposed Disturbance Footprint .....	62
4.4	Project Schedule.....	65
4.4.1	Construction .....	65
4.4.2	Operations .....	65
4.4.3	Processing.....	65
4.4.4	Closure and Rehabilitation .....	65
4.5	Construction Activities .....	67
4.5.1	Processing Plant.....	67
4.5.2	Tailings Storage Facility .....	75
4.5.3	Accommodation Camp .....	80
4.5.4	Haul Road Upgrade.....	84
4.5.5	Landfill .....	88
4.5.6	Communications.....	88
4.6	Mining Operations .....	88
4.6.1	Overview.....	88
4.6.2	Mining Equipment .....	89
4.6.3	Mining Maintenance .....	90
4.7	Waste Rock Material .....	93
4.7.1	Rustlers Roost Waste Rock Dump Design.....	93
4.7.2	Quest 29 Waste Rock Dump Design .....	94
4.8	Transport and Traffic.....	98
4.9	Wastewater Discharge Requirements.....	98
4.9.1	Rustlers Roost.....	98
4.9.2	Quest 29 .....	98
4.10	Water Use and Supply.....	99
4.10.1	Water Demand .....	99
4.10.2	Rustlers Roost Water Management System .....	99
4.10.3	Quest 29 Water Management System .....	100
4.10.4	Sewage Waste .....	100
4.10.5	Site Water Management to Prevent Biting Insects.....	100
4.11	Energy Supply and Demand .....	103
4.11.1	Rustlers Roost.....	103

# Table of Contents

---

4.11.2	Quest 29 .....	103
4.12	Handling (Storage and Transport) of Hazardous Chemicals.....	103
4.13	Social and Economic.....	104
4.13.1	Workforce and Accommodation .....	104
4.13.2	Economic .....	104
4.14	Closure and Rehabilitation .....	104
4.15	Alternatives Assessment .....	106
4.15.1	Waste Rock Dumps.....	107
4.15.2	Tailings Storage Facility .....	107
4.15.3	Processing Plant.....	109
4.15.4	Accommodation Camp .....	109
4.15.5	Landfill .....	110
4.15.6	Haul Road .....	110
<b>Section 5 Existing Environment.....</b>		<b>112</b>
5.1	Natural Environment.....	112
5.1.1	Geology.....	112
5.1.2	Landform and Soils .....	115
5.1.3	Flora and Fauna .....	119
5.1.4	Hydrology .....	121
5.1.5	Groundwater .....	125
5.1.6	Climate.....	125
5.2	Significant Sites or Features .....	131
5.2.1	Communities .....	131
5.2.2	Culturally Important or Sacred Sites.....	131
5.2.3	Heritage Sites.....	131
5.2.4	Sites of Conservation Significance .....	131
5.2.5	Mary River Floodplain System and National Park.....	132
5.2.6	Adelaide River Floodplain System .....	132
5.3	Demography and Economy .....	134
<b>Section 6 Risk Assessment of Environmental Factors.....</b>		<b>135</b>
6.1	Introduction .....	135
6.2	Relevant Environmental Factors .....	135
6.3	Risk Assessment Process and Methodology .....	136
6.3.1	Risk Identification .....	136
6.3.2	Risk Matrix.....	139
6.3.3	Risk Treatment .....	143
6.3.4	Risk Evaluation and Assessment.....	143
6.3.5	Indirect and Cumulative Impact .....	148
<b>Section 7 Key Environmental Factors .....</b>		<b>155</b>
7.1	Terrestrial Environmental Quality.....	155
7.1.1	Environmental Values.....	156
7.1.2	Potential Impacts and Risks.....	172
7.1.3	Avoidance, Mitigation and Management .....	184

# Table of Contents

---

7.1.4	Monitoring and Reporting .....	189
7.1.5	Residual Impact .....	190
7.1.6	Predicted Outcome and Conclusions.....	198
7.1.7	Assumptions .....	198
7.2	Terrestrial Ecosystems .....	199
7.2.1	Environmental Values.....	199
7.2.2	Potential Impacts and Risks .....	235
7.2.3	Avoidance, Mitigation and Management .....	259
7.2.4	Monitoring and Reporting .....	265
7.2.5	Residual Impact .....	266
7.2.6	Predicted Outcome and Conclusions.....	272
7.2.7	Assumptions .....	272
7.3	Hydrological Processes.....	274
7.3.1	Environmental Values – Surface Water .....	274
7.3.2	Environmental Values – Groundwater .....	277
7.3.3	Potential Impacts and Risks .....	282
7.3.4	Avoidance, Mitigation and Management .....	300
7.3.5	Monitoring and Reporting .....	305
7.3.6	Residual Impact .....	305
7.3.7	Predicted Outcome and Conclusions.....	312
7.3.8	Assumptions .....	312
7.4	Inland Water Environmental Quality .....	313
7.4.1	Environmental Values.....	314
7.4.2	Potential Impacts and Risks .....	337
7.4.3	Avoidance, Mitigation and Management .....	354
7.4.4	Monitoring and Reporting .....	360
7.4.5	Residual Impact .....	367
7.4.6	Predicted Outcome and Conclusions.....	375
7.4.7	Assumptions .....	375
7.5	Aquatic Ecosystems.....	376
7.5.1	Environment Values.....	376
7.5.2	Potential Impacts and Risk .....	401
7.5.3	Avoidance, Mitigation and Management .....	415
7.5.4	Monitoring and Reporting .....	419
7.5.5	Residual Impact .....	421
7.5.6	Predicted Outcome and Conclusions.....	427
7.5.7	Assumptions .....	427
7.6	Community and Economy .....	428
7.6.1	Environmental Values.....	428
7.6.2	Potential Impacts and Risks .....	445
7.6.3	Avoidance, Mitigation and Management .....	456
7.6.4	Monitoring and Reporting .....	460
7.6.5	Residual Impact .....	460
7.6.6	Predicted Outcome and Conclusions.....	461
7.6.7	Assumptions .....	464
7.6.8	Consultation .....	464

<b>Section 8 Other Environmental Themes and Factors</b> .....	<b>465</b>
8.1 Sea – Marine Ecosystems .....	469
8.1.1 Environmental Values.....	469
8.1.2 Potential Impacts and Risks .....	473
8.1.3 Avoidance, Mitigation and Management .....	473
8.1.4 Outcomes .....	474
8.2 Air – Atmospheric Processes .....	475
8.2.1 Legislative Requirements.....	475
8.2.2 Greenhouse Gas Assessment.....	477
8.2.3 Mitigation Measures .....	483
8.3 People – Human Health .....	485
8.3.1 Environmental Values.....	485
8.3.2 Potential Impacts and Risks .....	486
8.3.3 Avoidance, Mitigation and Management .....	487
8.3.4 Outcomes .....	490
<b>Section 9 Commonwealth Government Matters</b> .....	<b>492</b>
9.1 Environment Protection and Biodiversity Conservation Act 1999.....	492
9.2 Matters of National Environmental Significance (MNES) .....	493
9.2.1 Overview.....	493
9.2.2 Desktop and Field Surveys.....	497
9.2.3 Nationally Threatened Species .....	498
9.2.4 Migratory Species .....	504
<b>Section 10 Environmental Management</b> .....	<b>512</b>
10.1 Environmental Management System.....	512
10.2 Environmental Policy .....	513
10.3 Environmental Requirements .....	513
10.4 Roles and Responsibilities .....	514
10.4.1 Overview.....	514
10.4.2 Design and Construction Works .....	514
10.5 Incident Reporting, Management and Corrective Actions.....	516
10.5.1 Incident Reporting and Management.....	516
10.5.2 Corrective Actions .....	517
10.6 Education and Training .....	519
10.7 Environmental Inspections and Audits .....	520
10.7.1 Inspections.....	520
10.7.2 Audits.....	521
10.8 Communication and Reporting .....	522
10.8.1 Project Internal.....	522
10.8.2 Project External .....	523
10.8.3 Contractor Monthly Reporting .....	523
10.8.4 Records of Environmental Activities.....	524
10.8.5 Documentation, Document Control and Records.....	524
10.9 Performance Outcomes and Indicators .....	525

10.10	Continual Improvement .....	526
<b>Section 11 Holistic Impacts .....</b>		<b>527</b>
11.1	Indirect and Cumulative Impact Assessment .....	527
11.2	Consideration of Project Against Legislated Principles and Duties .....	540
11.2.1	Ecologically Sustainable Development .....	540
11.2.2	Waste Management Hierarchy .....	544
11.2.3	Ecosystem-Based Management .....	545
11.2.4	Impacts of a Changing Climate .....	545
11.2.5	General Duty of Proponents .....	545
<b>Section 12 Conclusion of Predicted Impacts .....</b>		<b>547</b>
<b>Section 13 References .....</b>		<b>558</b>
Executive Summary .....		558
Section 1 to 4 .....		558
Section 5 – Existing Environment .....		560
Section 6 – Risk Assessment of Environmental Factors .....		561
Section 7 – Key Environmental Factors .....		561
Section 8 – Other Environmental Themes and Factors .....		576
Section 9 – Commonwealth Government Matters .....		577
Section 10 – Environmental Management .....		580
Section 11 – Holistic Impacts .....		580
Section 12 – Conclusion and Predicted Impacts .....		581

## Figures

Figure 1-1	Project Location and Regional Setting.....	5
Figure 1-2	Organisational Structure .....	7
Figure 1-3	Primary Gold Environmental Policy.....	8
Figure 1-4	Rustlers Roost and Quest 29 Project Location .....	11
Figure 1-5	Regional Exploration and Mineral Leases.....	12
Figure 1-6	Existing Infrastructure and Previous Disturbance at Rustlers Roost .....	17
Figure 1-7	Existing Infrastructure and Previous Disturbance at Quest 29.....	18
Figure 2-1	Components of the Northern Territory Offsets Framework .....	34
Figure 4-1	Rustlers Roost Existing and Proposed Disturbance Footprint .....	57
Figure 4-2	Quest 29 Existing and Proposed Disturbance Footprint.....	58
Figure 4-3	Geology and Structures of the Mount Bunday Area (GR Engineering 2021).....	60
Figure 4-4	Rustlers Roost Proposed Site Layout.....	63
Figure 4-5	Quest 29 Proposed Site Layout .....	64
Figure 4-6	Project Timeline .....	66
Figure 4-7	Processing Plant Layout.....	70
Figure 4-8	Processing Plant Circuit .....	72
Figure 4-9	Accommodation Camp Layout .....	82
Figure 4-10	Indicative Wastewater Treatment Plant Layout.....	83
Figure 4-11	Indicative Haul Road Cross-section Design.....	85
Figure 4-12	Project Proposed Haul Road - Overview A Rustlers Roost.....	86
Figure 4-13	Project Proposed Haul Road - Overview B Quest 29 .....	87
Figure 4-14	Rustlers Roost Pit Designs and Proposed Mining Stages.....	91
Figure 4-15	Quest 29 Pit Design and Proposed Mining Stages .....	92
Figure 4-16	Rustlers Roost Proposed Final Waste Rock Dump Designs .....	96
Figure 4-17	Quest 29 Proposed Final Waste Rock Dump Designs .....	97
Figure 4-18	Rustlers Roost Water Management Schematic.....	101
Figure 4-19	Quest 29 Water Management Schematic .....	102
Figure 4-20	Assessment Approach for Considering Alternatives.....	106
Figure 4-21	Tailings Storage Facility Drainage Arrangement.....	108
Figure 4-22	Alternative TSF, Landfill and Haul Road Locations Assessed .....	111
Figure 5-1	Geological Map of the Pine Creek Inlier .....	114
Figure 5-2	Archaean to Early Proterozoic Stratigraphy and Lithological Descriptions .....	114
Figure 5-3	Map of Rustlers Roost and Quest 29 Topography and Soils.....	118
Figure 5-4	Vegetation Types and Riparian Areas.....	120
Figure 5-5	Map of Project Area Hydrology (North) .....	123
Figure 5-6	Map of Project Area Hydrology (South) .....	124
Figure 5-7	Annual Regional Average Evaporation .....	126
Figure 5-8	Mean Monthly Rainfall and Evaporation Data at nearest BoM Station (Source: BoM 2021).....	127
Figure 5-9	Rustlers Roost Intensity Frequency Duration Curves .....	128
Figure 5-10	Mean Monthly Maximum and Minimum Temperature at nearest BoM Station (Source: BoM 2021) .....	129
Figure 5-11	Major Seasonal Rainfall Zones and Climate Classification (Source: BoM 2021) .....	130
Figure 5-12	Annual Wind Roses for Darwin Airport (Source: BoM 2021).....	130
Figure 5-13	Surrounding Significant Sites and Features .....	133
Figure 6-1	Project Risk Assessment Methodology.....	138
Figure 6-2	Project and Actions Considered for Cumulative Impacts .....	152
Figure 7-1	Land Systems Relevant to the Project Area.....	157
Figure 7-2	Rustlers Roost and Quest 29 Topography and Elevation.....	158

Figure 7-3	Soils Types Relevant to the Project Area .....	162
Figure 7-4	Land Units Relevant to the Project Area .....	166
Figure 7-5	Existing Disturbance .....	171
Figure 7-6	Vegetation Types in the Region.....	202
Figure 7-7	Broadscale Mapping of Vegetation Types within Project Area .....	203
Figure 7-8	Locations of Riparian Survey Areas (EcOz 2020a).....	206
Figure 7-9	Threatened Flora Records and Flora Survey Locations.....	210
Figure 7-10	Map of Modelled Distribution of Threatened Flora Species .....	211
Figure 7-11	Map of <i>Helicteres macrothrix</i> Survey Tracks at Rustlers Roost .....	213
Figure 7-12	Map of <i>Helicteres macrothrix</i> Survey Tracks at Quest 29.....	214
Figure 7-13	Map of modelled habitat for <i>Styloidium ensatum</i> and survey location .....	216
Figure 7-14	Location of Weeds Within and Surrounding Project Area .....	220
Figure 7-15	Fauna Field Survey Locations and Conservation Significant Species Records .....	222
Figure 7-16	Fauna Surveys from November 2016 and May 2017 (LES 2017a) .....	226
Figure 7-17	Map of the Project Area in relation to the Mary River Coastal Floodplain.....	234
Figure 7-18	Direct Vegetation and Habitat Disturbance .....	236
Figure 7-19	Surrounding Mining and Extractive Industry Projects .....	253
Figure 7-20	Areas of Influence for Cumulative Impact.....	254
Figure 7-21	Regional Hydrological Features .....	276
Figure 7-22	Mary River Groundwater and Surface Water Beneficial Use Areas .....	281
Figure 7-23	Rustlers Roost 1% AEP Flood Inundation .....	291
Figure 7-24	Rustlers Roost 1% AEP Flood Inundation .....	291
Figure 7-25	Regional Site Map and Groundwater Model Domain.....	293
Figure 7-26	Groundwater Model Grid and Boundary Conditions.....	294
Figure 7-27	Groundwater Model Predicted Extents.....	295
Figure 7-28	Cumulative Groundwater Drawdown Extents.....	297
Figure 7-29	Mary River Groundwater and Surface Water Beneficial Use Areas .....	317
Figure 7-30	Inland Water Downstream Environmental Values and Surface Water Beneficial Uses .....	318
Figure 7-31	Existing Upstream Surface Water and Groundwater Monitoring Sites .....	322
Figure 7-32	Existing Downstream Surface Water Monitoring Sites.....	323
Figure 7-33	Piper Diagram for Rustlers Roost and Quest 29 Surface Water Ionic Composition .....	329
Figure 7-34	Piper Diagram for Rustlers Roost and Quest 29 Groundwater Ionic Composition .....	330
Figure 7-35	Summary of Existing Inland Water Quality at Sampling Locations .....	333
Figure 7-36	Proposed Ongoing Monitoring Sites – Upstream.....	365
Figure 7-37	Proposed Ongoing Monitoring Sites – Downstream .....	366
Figure 7-38	Regional Overview of Aquatic Features.....	377
Figure 7-39	Project Area Aquatic Features.....	378
Figure 7-40	Regional Hydrogeological Features .....	380
Figure 7-41	Stream Orders Relevant to the Project Area .....	381
Figure 7-42	Permanent Surface Water Features .....	383
Figure 7-43	Survey Sites Related to Aquatic Ecology.....	388
Figure 7-44	Occurrences of Aquatic Related Threatened Fauna .....	397
Figure 7-45	Groundwater Dependent Ecosystem Mapping .....	400
Figure 7-46	Surrounding Projects with Potential Cumulative Aquatic Ecology Impacts.....	414
Figure 7-47	Project Setting and Surrounding Activities.....	430
Figure 7-48	Northern Territory Gross Regional Product.....	437
Figure 7-49	Relative socio-economic disadvantage.....	441
Figure 7-50	Relative socio-economic advantage and disadvantage .....	441
Figure 7-51	Economic resources .....	441

Figure 7-52	Education and occupation .....	441
Figure 7-53	Surrounding Mining and Extractive Industry Projects .....	444
Figure 8-1	Mary River and Adelaide River Costal Floodplains .....	472
Figure 8-2	Total Annual CO <sub>2</sub> -e Emission per each Project Activity .....	482
Figure 9-1	Matters of National Environmental Significance Occurrence .....	496
Figure 10-1	Primary Gold's Environmental Management System for the Project.....	512
Figure 10-2	Primary Gold's Environmental Management System Documentation Structure for the Project.....	513
Figure 10-3	Primary Gold's Environmental Incident Management Process for the Project .....	518
Figure 11-1	Surrounding Activities with Potential Indirect or Cumulative Impacts.....	528
Figure 11-2	Potential Indirect and Cumulative Interactions with Surrounding Projects and Activities.....	529

## Plates

Plate 1-1	Existing Flooded Rustlers Roost Pit .....	15
Plate 1-2	Remaining Tanks from Former Processing Plant at Rustlers Roost .....	15
Plate 1-3	Existing Waste Rock Dump at Rustlers Roost .....	15
Plate 1-4	Existing Heap Leach Pad at Rustlers Roost .....	15
Plate 1-5	Existing Zamu Pit with Regrowth at Quest 29 .....	16
Plate 1-6	Existing Zamu Pit at Quest 29 .....	16
Plate 1-7	Remaining Heap Leach Pond at Quest 29.....	16
Plate 1-8	Remaining Heap Leach Pad at Quest 29.....	16
Plate 4-1	Indicative Power Station .....	73
Plate 7-1	Rustlers Roost Heap Leach Pad Erosion, Red Line Indicates Gap in Existing Berm.....	169
Plate 7-2	Rustlers Roost Heap Leach Pad Erosion .....	169
Plate 7-3	Rustlers Roost Heap Leach Pad, Intact Erosion Control Berm .....	170
Plate 7-4	Vegetation in Land Unit 2b characteristic of Rustlers Roost site.....	204
Plate 7-5	Vegetation in Land Unit 2b characteristic of Rustlers Roost site.....	204
Plate 7-6	Vegetation in Land Unit 2a in Central Quest 29 WRD .....	204
Plate 7-7	Vegetation in Land Unit 6a Quest 29 Zamu Pit.....	204
Plate 7-8	Upstream Riparian Vegetation of Marrakai Creek Tributary.....	207
Plate 7-9	Downstream Riparian Vegetation of Marrakai Creek Tributary .....	207
Plate 7-10	Upstream Riparian Vegetation of Mount Bunday Creek Tributary .....	207
Plate 7-11	Downstream Riparian Vegetation of Mount Bunday Creek Tributary .....	207
Plate 7-12	<i>Helicteres macrothrix</i> Leaves and Flowers .....	212
Plate 7-13	Photographs of <i>Stylidium ensatum</i> Leaves and Flower .....	215
Plate 7-14	Photograph of <i>Schoutenia ovata</i> .....	217
Plate 7-15	Rustlers Roost Annie's dam .....	382
Plate 7-16	Rustlers Roost Pit Lake .....	382
Plate 7-17	Rustlers Roost Heap Leach Pond .....	382
Plate 7-18	Quest 29 Zamu Pit .....	382
Plate 7-19	Mount Bunday Creek, Site SWTG1A.....	390
Plate 7-20	Mount Bunday Creek, Site MBC01 .....	390
Plate 7-21	Mount Bunday Creek, Site SWTG3 .....	390
Plate 7-22	Coulter Creek, Site CC02.....	390
Plate 7-23	RRMCUS Marrakai Creek Control Upstream from Site.....	391
Plate 7-24	RRMCDS Marrakai Creek Tributary Downstream from Site .....	391
Plate 7-25	RRSW23 Mount Bunday Creek Tributary Downstream from the Rustlers Roost Heap Leach Pad.....	391
Plate 7-26	Q29SW2 Mount Bunday Creek Downstream .....	391
Plate 7-27	RP8-DS Drainage Line Directly Adjacent to South of Heap Leach Pad.....	392

Plate 7-28	RP6-US Creek Downstream of Annie’s Dam, Marrakai Creek Catchment .....	392
------------	--	-----

## Tables

Table 1-1	Proponent Contact Details .....	6
Table 1-2	Consultant Contact Details .....	6
Table 1-3	Pastoral Leasehold Land Details .....	8
Table 1-4	PGO Mineral Lease Details .....	9
Table 1-5	Regional Exploration and Mineral Leases.....	10
Table 1-6	Construction and Operational Components of Proposed Action .....	19
Table 1-7	Draft EIS Structure.....	22
Table 1-8	Key Companies Involved in the Draft EIS.....	22
Table 1-9	Summary Cross-Reference Table for ToR Requested Additional Information .....	23
Table 1-10	Vegetation Clearing Comparison .....	28
Table 1-11	Rustlers Roost Referral Infrastructure Layout and Draft EIS Infrastructure Layout Disturbance Comparison .....	29
Table 2-1	Summary of Other Legislation and Approvals Applicable to the Project.....	36
Table 3-1	Key Project Stakeholders.....	43
Table 3-2	IAP2 Levels of Engagement .....	45
Table 3-3	Different Depths of Engagement / Communication .....	46
Table 3-4	Engagement Activities by Stakeholder Groups.....	47
Table 3-5	Stakeholder Engagement to Date and Issues Raised.....	49
Table 3-6	Consultation Phases .....	52
Table 4-1	Project Ore Reserve Summary.....	59
Table 4-2	Existing Disturbance Footprint within the Project Area .....	61
Table 4-3	Anticipated Power Station Configuration .....	73
Table 4-4	Tailings Storage Facility Design Parameters .....	75
Table 4-5	ANCOLD Tailings Storage Facility Design Parameters (minimum) .....	77
Table 4-6	Project Haul Road Design Criteria .....	84
Table 4-7	Mining and Processing Equipment .....	89
Table 4-8	Rustlers Roost Pit, Annie Oakley and Annie’s Dam Pit Waste Volumes by Weathering Zone .....	93
Table 4-9	Estimate of NAF and PAF Waste Material Quantities at Rustlers Roost.....	94
Table 4-10	Quest 29 Pit Waste Volumes by Weathering Zone .....	94
Table 4-11	Quest 29 Pit Waste Material Volumes and Placement.....	94
Table 4-12	Estimate of NAF and PAF Waste Material Quantities at Quest 29 .....	95
Table 4-13	Proposed Surface Water Infrastructure and Conceptual Storage Capacity.....	100
Table 4-14	Hazardous Materials and Storage Volumes for Processing Activities.....	103
Table 4-15	Project Closure Objectives.....	105
Table 5-1	Land Units of the Project Area .....	116
Table 5-2	Description of Vegetation Types for Rustlers Roost and Quest 29 Project Areas .....	119
Table 6-1	Relevant Environmental Factors and Objectives.....	136
Table 6-2	Qualitative Risk Analysis Matrix .....	139
Table 6-3	Risk Range .....	139
Table 6-4	Definition of Likelihood Classification .....	139
Table 6-5	Description of Risk Classification .....	140
Table 6-6	Consequence Classification .....	141
Table 6-7	Level of Certainty .....	143
Table 6-8	Identified Risks and Relevant Factors.....	144
Table 6-9	Summary of Risks .....	147
Table 6-10	Assigned Classification of Projects relevant to Cumulative Impacts .....	153

Table 7-1	Predominant Land Systems in the Project Area .....	156
Table 7-2	Soil Erodibility and Emerson Class from Collected Soil Samples in Disturbed Areas .....	160
Table 7-3	Erosion Risk and Corresponding Land Use Suitability Classes, Modified from NT Land Suitability Guidelines .....	161
Table 7-4	Description of Land Units and Soils for the Project Area.....	163
Table 7-5	Potential Acidity of Site Minerals .....	168
Table 7-6	Potential Sources of Impact to Terrestrial Environmental Quality .....	172
Table 7-7	Annual Erosion Risk .....	178
Table 7-8	Hazardous Chemicals Stored on the Mine Site.....	179
Table 7-9	Assessment of Cumulative Impacts to Terrestrial Environmental Quality .....	182
Table 7-10	Avoidance, Mitigation and Management Measures .....	184
Table 7-11	Terrestrial Environmental Quality Residual Impact Assessment Summary .....	191
Table 7-12	Description of Vegetation Types for the Project Area .....	200
Table 7-13	Introduced Flora Species Recorded During Surveys .....	218
Table 7-14	Likelihood of Assessment Summary for Fauna relevant to the Project Area .....	223
Table 7-15	Mapped Vegetation Clearing Extent for Construction and Mining Operations.....	235
Table 7-16	Potential Sources of Impact to Impact to Terrestrial Ecosystems .....	237
Table 7-17	Mapped Vegetation and Clearing Extents .....	243
Table 7-18	Assessment of Cumulative Impacts to Terrestrial Ecosystems.....	255
Table 7-19	Avoidance, Mitigation and Management Measures .....	259
Table 7-20	Terrestrial Ecology Residual Impact Assessment Summary .....	267
Table 7-21	Rustlers Roost and Quest 29 Surface Water Catchments, Modelled Baseline, and Future Discharge .....	275
Table 7-22	Rustlers Roost Groundwater Levels .....	278
Table 7-23	Quest 29 Groundwater Levels .....	279
Table 7-24	Potential sources of impacts to hydrological processes.....	282
Table 7-25	Assessment of Cumulative Impacts to Hydrological Processes .....	298
Table 7-26	Avoidance, Mitigation and Management Measures for Hydrological Processes .....	300
Table 7-27	Overview of Pit Dewatering and Mining Phases.....	304
Table 7-28	Hydrological Processes Residual Impact Assessment Summary.....	307
Table 7-29	Rustlers Roost – Marrakai Creek Catchment – Surface Water Monitoring Locations .....	319
Table 7-30	Rustlers Roost Mount Bunday Creek Catchment Surface Water Sampling Locations.....	319
Table 7-31	Quest 29 Mount Bunday Creek Catchment – Surface Water Monitoring Locations .....	320
Table 7-32	Quest 29 McKinlay River Catchment – Surface Water Monitoring Locations .....	320
Table 7-33	Accommodation camp – Coulter Creek Surface Water Monitoring Sites .....	321
Table 7-34	Toms Gully Mine – Lower Mount Bunday Creek Surface Water Monitoring Sites.....	321
Table 7-35	Baseline Marrakai Creek Catchment Water Quality Parameters .....	324
Table 7-36	Baseline Mount Bunday Creek Catchment Water Quality Parameters - Upstream .....	325
Table 7-37	Baseline Mount Bunday Creek Catchment Water Quality Parameters at Quest 29.....	326
Table 7-38	Baseline McKinlay River Catchment Water Quality Parameters at Quest 29.....	326
Table 7-39	Baseline Water Quality at Toms Gully for Lower Mount Bunday Creek Catchment .....	327
Table 7-40	Baseline Water Quality Proposed Accommodation Camp for Coulter Creek.....	328
Table 7-41	Sediment Sampling Locations and Descriptions .....	331
Table 7-42	Laboratory Result Summary for Sediment Toxicant DGV* Covered Dissolved Metals.....	332
Table 7-43	Laboratory Result Summary for Dissolved Metals (Without Toxicant Default Guideline Values) .....	332
Table 7-44	Current Groundwater Monitoring Bores .....	334
Table 7-45	Baseline Groundwater Quality Parameters at Rustlers Roost .....	335
Table 7-46	Baseline Groundwater Quality Parameters at Quest 29 .....	336
Table 7-47	Tabulated Conceptual Site Model for Inland Water Environmental Quality Contaminant Pathways .....	338
Table 7-48	Potential sources of impact to Inland Water Environmental Quality .....	341
Table 7-49	Potential Cumulative Impact to Inland Water Environmental Quality .....	352

Table 7-50	Potential Impacts to Inland Water Environmental Quality and Avoidance, Mitigation, and Management Measures .....	354
Table 7-51	Proposed Surface Water Monitoring Locations .....	361
Table 7-52	Proposed Groundwater Monitoring Locations .....	362
Table 7-53	Proposed Sediment Monitoring Locations .....	363
Table 7-54	Inland Water Environmental Quality Residual Impact Assessment Summary .....	368
Table 7-55	Aquatic Ecosystem Relevant Fauna Identified in EPBC PMST and NT Listed Threatened Species .....	384
Table 7-56	Aquatic Ecosystem, Riparian, Macroinvertebrate and Sediment Sampling Sites .....	386
Table 7-57	Representative Sampling Sites for Fish, Macroinvertebrates and Riparian Vegetation .....	389
Table 7-58	Potential Sources of Impact to Aquatic Ecosystems.....	401
Table 7-59	Assessment of Cumulative Impacts to Aquatic Ecosystems .....	411
Table 7-60	Potential impacts to Aquatic Ecosystems and avoidance, mitigation, and management measures.....	415
Table 7-61	Proposed Biological Monitoring Locations .....	420
Table 7-62	Aquatic Ecosystem Residual Impact Assessment Summary .....	422
Table 7-63	Population Statistics .....	433
Table 7-64	Indigenous Population.....	433
Table 7-65	Labour Force Participation .....	434
Table 7-66	Top Industries of Employment .....	434
Table 7-67	Transport Related Community Data .....	435
Table 7-68	Arnhem Highway Traffic Data .....	436
Table 7-69	Vehicle Serious Injury and Fatality Statistics .....	436
Table 7-70	Underlying Regional Economic Trends .....	438
Table 7-71	Potential Sources of Impact to Community and Economy .....	445
Table 7-72	Mining Capital Expenditure .....	453
Table 7-73	Unit Mining Costs by Cost Centre.....	454
Table 7-74	Total Operating Cost by Year (\$M) .....	455
Table 7-75	Avoidance, Mitigation and Management Measures .....	456
Table 7-76	Community and Economy Residual Impact Assessment Summary .....	462
Table 8-1	Other Environmental Factors .....	466
Table 8-2	Avoidance, Mitigation and Management .....	473
Table 8-3	NGER Reporting Thresholds .....	476
Table 8-4	Emission Factor .....	479
Table 8-5	Construction Annual Emissions (Tonnes CO <sub>2</sub> -e) .....	480
Table 8-6	Operational Annual Emissions (Tonnes CO <sub>2</sub> -e).....	481
Table 8-7	Summary of Annual Emissions (Tonnes CO <sub>2</sub> -e) .....	482
Table 8-8	Avoidance, Mitigation and Management Measures .....	488
Table 9-1	Summary of the Potential Impacts of MNES .....	493
Table 9-2	Assessment of Likelihood of Occurrence and Potential Significant Impact of Fauna Species .....	499
Table 9-3	Migratory Species Identified in the PMST and Fauna Atlas as Occurring, or Potentially Occurring, within 25 km of the Project Area.....	504
Table 9-4	Assessment of the Likelihood of Occurrence for Species in the Referral Guideline for 14 Birds Listed as Migratory Species Under the EPBC Act .....	507
Table 9-5	Potentially Occurring Migratory Species Significant Impact Threshold as per Draft Referral Guideline for 14 Birds Listed as Migratory Under the EPBC Act .....	510
Table 9-6	Assessment Against Significant Impact Criteria: Migratory Species Contained in the Draft Referral Guidelines for 14 Birds Listed as Migratory Under the EPBC Act .....	510
Table 10-1	Draft Environmental Inspection Regime .....	514
Table 10-2	Preliminary Training and Competency Matrix.....	519
Table 10-3	Draft Environmental Inspection Regime .....	521
Table 10-4	Project Internal Reporting .....	522

Table 10-5	External Environmental Reporting Requirements .....	523
Table 11-1	Summary of Potential Indirect and Cumulative Impacts .....	530
Table 11-2	Guiding Principles of Ecologically Sustainable Development Addressed .....	541
Table 11-3	General Duty of Proponents Addressed .....	545
Table 12-1	Assessment of Project Against NT EPA Environmental Factor Objective .....	548

## Appendices

<b>Appendix A</b>	<b>Stakeholder Engagement Plan .....</b>	<b>582</b>
<b>Appendix B</b>	<b>Risk Assessment Register .....</b>	<b>584</b>
<b>Appendix C</b>	<b>EIS Terms of Reference.....</b>	<b>586</b>
<b>Appendix D</b>	<b>Materials Characterisation Study.....</b>	<b>588</b>
<b>Appendix E</b>	<b>Cross-Reference ToR to the EIS.....</b>	<b>590</b>
<b>Appendix F</b>	<b>TSF Dam Break and Consequence Assessment .....</b>	<b>592</b>
<b>Appendix G</b>	<b>Traffic Management Plan .....</b>	<b>594</b>
<b>Appendix H</b>	<b>Water Balance and Groundwater Modelling Report.....</b>	<b>596</b>
<b>Appendix I</b>	<b>Water Management Plan .....</b>	<b>598</b>
<b>Appendix J</b>	<b>Draft Mine Closure Plan .....</b>	<b>600</b>
<b>Appendix K</b>	<b>Ecological Flora and Fauna Reports.....</b>	<b>602</b>
<b>Appendix L</b>	<b>Erosion and Sediment Control Plans .....</b>	<b>604</b>
<b>Appendix M</b>	<b>Vegetation Survey Report .....</b>	<b>606</b>
<b>Appendix N</b>	<b>Hydrology and Flood Assessment Report.....</b>	<b>608</b>
<b>Appendix O</b>	<b>Pit Stratification Study .....</b>	<b>610</b>
<b>Appendix P</b>	<b>Pit Lake Assessment Report.....</b>	<b>612</b>
<b>Appendix Q</b>	<b>Macroinvertebrate and Sediment Monitoring .....</b>	<b>614</b>
<b>Appendix R</b>	<b>Ecological Searches .....</b>	<b>616</b>
<b>Appendix S</b>	<b>Aquatic Ecology Survey Reports .....</b>	<b>618</b>
<b>Appendix T</b>	<b>Acid and Metalliferous Drainage Management Plan .....</b>	<b>620</b>
<b>Appendix U</b>	<b>Commitment Register .....</b>	<b>622</b>

## Document History and Status

Revision	Date issued	Reviewed by	Approved by	Date approved	Revision type
A	05/09/2021	P.Davey, T.Mitchell	P.Davey	05/09/2021	Draft
B	24/09/2021	S.Ley; T.Mitchell	P.Davey	30/09/2021	Draft
0	22/10/2021	P.Davey	P.Davey	22/10/2021	Final

## Distribution of Copies

Version	Date issued	Quantity	Electronic	Issued to
Draft, Rev A	05/09/2021	1	Word	Primary Gold Ltd
Rev B	30/09/2021	1	Word	Primary Gold Ltd
Rev 0	22/10/2021	1	PDF	Primary Gold Ltd

<b>Last Saved:</b>	25 October 2021
<b>File Name:</b>	1001087_Rustlers-Roost-Quest-29-Draft EIS_Final_Oct 2021
<b>Author:</b>	CDM Smith
<b>Project Manager:</b>	Paul Davey
<b>Client:</b>	Primary Gold Ltd (PGO)
<b>Document Title:</b>	<b>Rustlers Roost and Quest 29 Open-Cut Mine Redevelopment: Draft Environmental Impacts Statement (EIS)</b>
<b>Document Version:</b>	Rev 0
<b>Project Number:</b>	1001087

### Key Project Terms

Term	Definition
Adaptive Management	Systematic process for incrementally improving management practices by learning from the outcomes of past and current practices.
Carbon in Leach	This process uses a dilute alkaline cyanide solution to leach (dissolve) gold from the ore material. Activated carbon removes gold out of dilute cyanide solution by adsorption (sticking). The leaching agent and activated carbon are added together in a slurry of ore and water.
Development Envelope	Defined as the maximum area within which the Project footprint could occur. The development envelope for the Project encompasses 790 ha, inclusive of Rustlers Roost, Quest 29, the accommodation camp and haul road.
Environmental Aspect	An element of the Primary Gold's activities, products or services that can interact with the environment.
Environmental Impact	Change to the environment whether adverse or beneficial, wholly or partially resulting from the Primary Gold's environmental aspects. Environmental impacts can be caused directly or indirectly from a Project activity or cumulatively with other non-Project related activities in a set area.
Environmental Factor	The NT EPA listed environmental objectives to identify environmental matters that have value to the Northern Territory and that need to be protected; and to state the objective to be achieved for each matter. The NT EPA has prepared these environmental objectives and organised these in structured divisions of the environment, called environmental factors.
Existing Disturbance Footprint	Defined as the direct disturbance area from known historical activities associated with the Rustlers Roost, Quest 29, accommodation camp and haul road areas. For Rustlers Roost and Quest 29 this is taken from the existing Mine Management Plans. The existing direct disturbance footprint encompasses 169.4ha within the development envelope.
Heap Leach Pad	Existing areas where historic mining placed ore for processing via a leaching solution to dissolve and capture the mineral. The pads contain the remaining material.
Maximum Vegetation Clearing Extent	The maximum extent of native vegetation clearing proposed for the Project based on mapped vegetation extent layers which account for historic anthropogenic disturbances to the development envelope (e.g. historic mining and pastoral activities). This area constitutes a total of 368.86 ha.
Project	The Project includes the expansion of existing pits, waste rock landforms, water storage dams and internal roads in both the Rustlers Roost and Quest 29 MLs. Two new pits will be constructed at Rustlers Roost and new infrastructure includes an onsite processing plant, a tailings storage facility, a landfill, laydown area, magazine, administration office, accommodation camp and groundwater bores for water supply. The Project is inclusive of an expanded connecting haul road between the non-contiguous extraction areas and an accommodation camp.
Project Area	The Project area is defined as wholly including ML1083 (Rustlers Roost), ML 29783 (Quest 29), ML 29814 (accommodation camp) and the connecting haul road. The entire Project area covers 1,143.25 ha.
Direct Disturbance Footprint	Defined as the direct disturbance area based on the current proposed infrastructure and material placement inclusive of Rustlers Roost, Quest 29, the accommodation camp and haul road. This area covers both historically disturbed and undisturbed areas. The disturbance footprint encompasses 532.84 ha within the Project area.
Significant Impact	A significant impact of an action is an impact of major consequence having regard to: (a) the context and intensity of the impact; and (b) the sensitivity, value and quality of the environment impacted on and the duration, magnitude and geographic extent of the impact.
Study Area	Refers to the area of survey or investigation for a specific study. This area may be beyond the Project area or development envelope.
Tailings Storage Facility	A specially engineered and constructed impoundment into which tailings (residue) from the ore processing plant is deposited for placement in perpetuity. The storage facility is constructed with confining embankments consisting of earthen material (e.g. rock and soil) and capped following closure.
Waste Rock Dump	An engineered and constructed impoundment into which overburden from the mining process is placed for safe storage in perpetuity.

## Acronyms, Abbreviations and Units

Abbreviation, Acronym or Unit	Definition
\$m	Million dollars
%	Percentage
+ve	Assessment of positive
µS	Microsiemens
4WD	Four-wheel drive
AADT	Average Annual Daily Traffic
AAS	Atomic Absorption Spectrophotometer
AAPA	Aboriginal Areas Protection Authority
AARL	Anglo American Research Laboratory
ABS	Australian Bureau of Statistics
AE	Aquatic Ecosystems
AEP	Annual Exceedance Probability
AFANT	Amateur Fishermen's Association of the Northern Territory
AHD	Australian Height Datum
ALA	Atlas of Living Australia
ALARP	As Low As Reasonably Practicable
AMD	Acid and Metalliferous Drainage
ANC	Acid Neutralising Capacity
ANCOLD	Australian National Committee on Large Dams
ANFO	Ammonium Nitrate
ANZG	Australia and New Zealand Government
ARI	Average Recurrence Interval
ARPANSA	Australian Radiation Protection and Nuclear Safety Agency
AS	Australian Standard
ASRIS	Australian Soil Resource Information System
ASX	Australian Stock Exchange
AS/NZS	Australian/New Zealand Standards
AUSRIVAS	Australian River Assessment System
BESS	Battery Energy Storage System
BoM	Bureau of Meteorology
BOO	Build-Own-Operate
BOOT	Build-Own-Operate-Transfer
Bq	Becquerel
BUD	Beneficial Use Declaration
CAD	Computer-Aided Design
CAPEX	Capital Expenditure
CCTV	Closed Circuit Television
CE	Community and Economy
CEO	Chief Operating Officer
CH <sub>4</sub>	Methane

## Distribution of Copies

Abbreviation, Acronym or Unit	Definition
CIL	Carbon in Leach
CO <sub>2</sub>	Carbon Dioxide
CO <sub>2</sub> -e	Carbon Dioxide Equivalent
COPC	Contaminant of Potential Concern
CSIRO	Commonwealth Scientific and Industrial Research Organisation
CSL	Compact Soil Liner
CSM	Conceptual Site Model
C&D	Construction and Demolition
C&I	Commercial and Industrial
DAWE	Department of Agriculture, Water and Environment (Cth) (current)
DEPWS	Department of Environment, Parks and Water Security (NT) (current)
DGV	Default Guideline Value
DIDO	Drive-in Drive-out
DITT	Department of Industry, Tourism and Trade (NT) (current)
DIWA	Directory of Important Wetlands of Australia
DO	Dissolved Oxygen
DotE	Department of the Environment (Cth) (former)
DotEE	Department of the Environment and Energy (Cth) (former)
EC	Electrical Conductivity
EH&S	Environment, Health and Safety
EIS	Environmental Impact Statement
EMP	Environmental Management Plan
EMS	Environmental Management System
EPA	Environment Protection Authority
EPBC Act	<i>Environment Protection and Biodiversity Conservation Act 1999</i>
EPL	Environment Protection Licence
EP Act	<i>Environment Protection Act 2019</i>
ERA	Energy Resources of Australia
ERP	Emergency Response Plan
ESCP	Erosion and Sediment Control Plan
ESD	Ecologically Sustainable Development
GDE	Groundwater Dependent Ecosystem
GGAP	Greenhouse Gas Abatement Plan
GHG	Greenhouse Gas
GJ	Gigajoule
GL	Gigalitre (1,000 Megalitres)
GPS	Global Positioning System
GRP	Gross Regional Product
GST	Goods and Services Tax
g/t	Grams Per Tonne
GV	Guideline Value
GWP	Global Warming Potential
ha	Hectare

Abbreviation, Acronym or Unit	Definition
HDPE	High Density Polyethylene
HEC-HMS	Hydrologic Modelling System
HFC	Hydrofluorocarbons
HP	Hydrological Processes
HSE	Health, Safety and Environment
IAP2	International Association for Public Participation
IBC	Intermediate Bulk Container
ID	Identification
IECA	International Erosion Control Association
IFC	International Finance Corporation
IPCC	Intergovernmental Panel on Climate Change
IPP	Independent Power Provider
ISO	International Organisation for Standardisation
IWEQ	Inland Water Environmental Quality
JORC	Joint Ore Reserve Committee
kL	Kilolitre
km	Kilometre
km <sup>2</sup>	Square Kilometre
kV	Kilovolt
L	Litre
L/s	Litre Per Second
LED	Light Emitting Diode
LiDAR	Light Detection and Ranging
LNG	Liquefied Natural Gas
LOM	Life-of-Mine
LPG	Liquefied Petroleum Gas
M	Million
m	Metre
m <sup>2</sup>	Metre squared
m <sup>3</sup>	Cubic metre
mAHD	Metres Australian Height Datum
mBGL	Metres Below Ground Level
MCP	Mine Closure Plan
MEDLI	Model for Effluent Disposal Using Land
mg	Milligram
ML	Mining Lease (Granted)
MLA	Mining Lease Application
mm	Millimetre
MMP	Mining Management Plan
MNES	Matter of National Environmental Significance
MP	Management Plan
mRL	Metres Reduced Level
Mt	Million Tonnes

## Distribution of Copies

Abbreviation, Acronym or Unit	Definition
Mtpa	Million Tonnes Per Annum
MW	Megawatt
N <sub>2</sub> O	Nitrous Oxide
NAF	Non-Acid Forming
NAPP	Net Acid Producing Potential
N/A	Not Applicable
NGER Act	<i>National Greenhouse Energy Reporting Act 2007</i>
NLC	Northern Land Council
NMD	Neutral Mine Drainage
NORM	Naturally Occurring Radioactive Material
NOI	Notice of Intent
NO <sub>2</sub>	Nitrogen Dioxide
NSESD	National Strategy for Ecologically Sustainable Development
NT	Northern Territory
NTG	Northern Territory Government
NTU	Nephelometric Turbidity Unit
NT Act	<i>Native Title Act 1993</i>
NVIS	National Vegetation Information System
OPEX	Operational Expenditure
PAF	Potentially Acid Forming
PASS	Potential Acid Sulfate Soil
PER	Public Environmental Report
PET	Plecoptera, Ephemeroptera and Trichoptera
PFC	Perfluorocarbon
PGO	Primary Gold Limited, a wholly owned subsidiary of Hanking Australia Investment Pty Ltd
PMF	Probable Maximum Flood
PMLU	Post Mining Land Use
PMST	Protected Matter Search Tool
PPL	Perpetual Pastoral Lease
Q	Quarter
RL	Reduced Level
RMP	Risk Management Plan
RO	Reverse Osmosis
ROM	Run of Mine
RRMPL	Rustlers Roost Mining Pty Ltd
RSWL	Reduced Standing Water Level
SA	Statistical Area
SD	Saline Drainage
SDS	Safety Data Sheet
SEP	Stakeholder Engagement Plan
SEIFA	Socio-Economic Indexes for Areas
SF <sub>6</sub>	Sulfur Hexafluoride
SGV	Site-Specific Guideline Value

## Distribution of Copies

Abbreviation, Acronym or Unit	Definition
SIGNAL	Stream Invertebrate Grade Number – Average Level
SoBS	Site of Botanical Significance
SoCS	Site of Conservation Significance
SSAN	Security Sensitive Ammonium Nitrate
SSC	State Suburb Code
SSTV	Site-Specific Trigger Values
STP	Sewage Treatment Plant
SWG	Stock Water Drinking Guidelines
SWL	Standing Water Level
t	Tonne
TAMS	Territory Asset Management Services
TARP	Trigger Action Response Plan
TBD	To Be Determined
TE	Terrestrial Ecosystems
TEC	Threatened Ecological Community
TEQ	Terrestrial Environmental Quality
Th	Thorium
TN	Total Nitrogen
ToR	Terms of Reference
TP	Total Phosphorus
TPWC Act	<i>Territory Parks and Wildlife Conservation Act 1976</i>
TSF	Tailings Storage Facility
TSS	Total Suspended Solids
TSSC	Threatened Species Scientific Committee
U	Uranium
UC	Uncertain
V	Volt
UNESCO	United Nations Educational, Scientific and Cultural Organisation
UNFCCC	United Nations Framework Convention on Climate Change
WCD	Water Control District
WDL	Waste Discharge Licence
WMP	Water Management Plan
WONS	Weed of National Significance
WRD	Waste Rock Dump
WTP	Water Treatment Plant
WWTP	Wastewater Treatment Plant

### 7.3 Hydrological Processes

<b>NT EPA Environmental Factor</b>	<b>Hydrological Processes</b>
<b>NT EPA Environmental Objective</b>	<i>Protect the hydrological regimes of groundwater and surface water so that environmental values including ecological health, land uses and the welfare and amenity of people are maintained.</i>
<b>Relevant Policy and Guidance</b>	<ul style="list-style-type: none"> <li>▪ Northern Territory Water Allocation Planning Framework (Policy) (Northern Territory Government 2020);</li> <li>▪ Guidelines on the Consequence Categories for Dams (ANCOLD 2012);</li> <li>▪ <i>Water Act 1992</i>; and</li> <li>▪ Water Stewardship, Leading Practice Sustainable Development Program for the Mining Industry (Australian Government 2016a).</li> </ul>

#### 7.3.1 Environmental Values – Surface Water

The Rustlers Roost site is located on a catchment divide (Figure 7-21). The eastern portion of surface water flows drain into the Mary River catchment via Mount Bunday Creek; and the western portion of flows drain into the Adelaide River via an unnamed tributary of Marrakai Creek.

The Rustlers Roost catchment is comprised of a series of ridges and dissected hills, which are drained by small steep rivulets. These systems converge into a single creek channel in the south-east of the site. The mining area has a small external catchment area of approximately 2.2 km<sup>2</sup>.

The Quest 29 Project area is located on the boundary of two upper sub-catchments within the Mary River regional catchment. The main catchment encompasses two drainage lines flowing south through the site, converging into one drainage line that flows south-east off the tenement boundary and in an easterly direction towards the McKinlay River.

All waterways within the Project area are ephemeral. Flows are intermittent and occur in direct response to rainfall. Stream flows predominantly occur during the wet season months from late November (first-flush) to April (recessional flows), with sustained creek flows for approximately four months (December to March). There are no permanent pools located within the Project areas during the dry season; however, isolated pools remain during early dry season further downstream in the catchments. Catchment boundaries and drainage lines are shown in Figure 7-35.

##### 7.3.1.1 Mount Bunday Creek

Surface hydrological regimes in Mount Bunday Creek are not significantly altered by any existing land use in the catchment, which is limited to pastoral grazing and the Mary River National Park. Past mining activities are unlikely to have significantly altered flows in any of the creeks downstream because those activities affect relatively small areas of land in the upper parts of the catchment that are a relatively minor contributor to stream flows.

A total of 66% (or 4.9 km<sup>2</sup>) of the Rustlers Roost ML 1083 and all of the accommodation camp is located within the headwaters of the Mount Bunday Creek catchment. Approximately 3.5% (or 0.1 km<sup>2</sup>) of Quest 29 ML 29783 (northern area heap leach infrastructure) drains north into Charlies Creek, a tributary of the upper Mount Bunday Creek, upstream of the Rustlers Roost portion of the Project area. The Project area covers 3.5% (or 5.8 km<sup>2</sup>) of the total ~170 km<sup>2</sup> catchment area of the Mount Bunday Creek.

## Section 7. Key Environmental Factors

Mount Bunday Creek is currently used as stock drinking water during the wet season, and the wet season flows and dry season pools support riparian and aquatic ecosystems. The nearest permanent billabong thought capable of providing suitable habitat for aquatic fauna is situated approximately 4 km directly north-east of the Rustlers Roost Project area (Figure 7-42).

### 7.3.1.2 Marrakai Creek

A total of 34% (or 2.6 km<sup>2</sup>) of Rustlers Roost ML 1083 (the western portion) is located within the headwaters of the Marrakai Creek catchment. The main ephemeral drainage line that receives surface water flows from the Project area has been dammed to create Annie's Dam, previously built as a pastoralist dam. The dam has a surface area of approximately 11 ha and without extraction, retains water throughout the dry season.

Surface water flows from this area, flow west into minor unnamed ephemeral drainage lines, which during the wet season flow into Marrakai Creek proper approximately 6 km downstream. Marrakai Creek discharges into the upper tidal reaches of the Adelaide River approximately 35 km downstream of the Project area.

### 7.3.1.3 McKinlay River


The remaining 96.5% (or 2.75 km<sup>2</sup>) of the Quest 29 ML 29783 falls within the McKinlay River catchment. Unnamed ephemeral drainage lines downstream of the site discharge to the east through floodplains towards the McKinlay River main branch, which is approximately 15 km downstream of the Project area. From this location, the McKinlay River flows north and discharges into the Mary River.

### 7.3.1.4 Project Area Catchment Stream Flows

There are no stream flow data for the tributaries and relevant creeks in the Project area. However, a hydrologic model was developed for each of the catchments at Rustlers Roost and Quest 29 to assess baseline environmental flows and future flows by application of a climate change scenario with changed catchment conditions resulting from mining (Primary Gold 2021a, Primary Gold 2021b). Overall, there was little difference between the baseline discharge and the modelled future scenario discharge, as well as the baseline peak flow (Q<sub>p</sub>) and the modelled future mean flow for all connected catchments (Table 7-21).

**Table 7-21 Rustlers Roost and Quest 29 Surface Water Catchments, Modelled Baseline, and Future Discharge**


Catchment	Mean Baseline Annual Discharge (GL)	Mean Scenario Annual Discharge (GL)	Baseline Peak Flow (Q <sub>p</sub> ) (m <sup>3</sup> s <sup>-1</sup> )	Mean Scenario Peak Flow (Q <sub>p</sub> ) (m <sup>3</sup> s <sup>-1</sup> )
Rustlers Roost east (Mount Bunday Creek)	3.7	3.8	2.4	2.3
Rustlers Roost west (Marrakai Creek)	1.9	2.5	0.7	0.8
Quest 29 north (Mount Bunday Creek)	0.5	0.5	1.6	1.7
Quest 29 south (McKinlay River)	1.7	1.7	5.0	5.8



Note: Beneficial Uses are stock water supply for that part of the waterway shown as **A** on the plan and acquatic ecosystem protection applies to the remainder of the waterway

R	Details	Date
1	Final	30/08/21
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

©COPYRIGHT CDM SMITH This drawing is confidential and shall only be used for the purpose of this project.			
DESIGNED	SS	CHECKED	TK
DRAWN	SS	CHECKED	TK
APPROVED	TK	DATE	30/08/21
Notes:			



**DISCLAIMER**  
CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

DATA SOURCE  
NT Government Open Source Data



FIGURE 7-21

**Regional Hydrogeological Features**

DRG Ref: 1001087-EIS-07-7.35

## Section 7. Key Environmental Factors

### 7.3.1.5 Inundation and Flood Occurrence

There are no records of significant flood events within the Project area. Hydrodynamic flood models have been used to assess the potential occurrence and impacts of flood and inundation events at Rustlers Roost (CDM Smith 2019a, Appendix N).

Due to previous mining activities the catchment area has been highly disturbed. This led to numerous areas, especially in the eastern section around the WRD, being prone to shallow ponding (< 0.2m). Rainfall would be likely to pond at these locations for a short time before either seeping into the soil or evaporating away. Furthermore, there is reasonable separation between disturbed and undisturbed areas of the site. The Rustlers Roost pit void acts as a terminal sink for a large portion of the catchment, including the WRD and previous mine infrastructure area. In addition, the gullies to the west of the heap leach pad and ponds drain freely to the outlet (i.e. site boundary), separated from the disturbed areas by bunds. Overall the site is unlikely to be adversely affected by flooding, as the undisturbed sections are largely free draining, and the disturbed sections drain mostly to the pit.

### 7.3.1.6 Beneficial Uses

The Mary River regional catchment has declared 'beneficial uses' under the *Water Act 1992*. The Mary River beneficial uses declaration (BUD) covers Rustlers Roost (with the exception of the western catchment encompassing Annie's dam) and the Quest 29 Project area. The declared beneficial uses for the Mary River surface water catchment are environment, riparian and cultural. These uses rely on the maintenance of stream flows and good water quality. The potential impact of mining activity on declared beneficial uses is taken into consideration by the NT Government when making decisions in relation to project approvals.

The Project areas are not directly covered by the Mount Bunday Creek BUD. The BUD commences approximately 13 km downstream of the Project areas. The declared beneficial uses for Mount Bunday Creek are aquatic ecosystem protection (for the upper and lower creek sections), and stock water supply for the middle 7.8 km section of the creek (downstream of Toms Gully Mine east of the Arnhem Highway).

### 7.3.1.7 Surface water Users

The Project area is located on pastoral leases with existing pits and dams that may be accessed by stock and fauna for drinking water. Flows in watercourses or permanent waterholes downstream of the mine sites, may also be accessed by stock and fauna. There are no known direct surface water users within the 5 km radius of the Project area.

## 7.3.2 Environmental Values – Groundwater

Groundwater information available for the Project area is limited to regional-scale aquifer information available from Tickell 2019 and historical site-specific information from previous operators of Rustlers Roost, Valdora (1994) and Greenbase (1997). In general, the regional groundwater system comprises of intermediate-scale aquifers associated with unconsolidated sediments and local-scale aquifers associated with fractured and weathered rocks. The Project area is situated near the northern flank of the Pine Creek Geosyncline. Aquifers, where they occur, are typically associated with increased structural deformation of the metasediments.

Groundwater Enterprises (2020) was commissioned to prepare a groundwater investigation plan, including aquifer hydraulic properties testing, for the Project area. A network of groundwater monitoring bores, as recommended by Groundwater Enterprises (2020), was installed during October 2020. Baseline groundwater monitoring will be undertaken on these investigation bores, which will provide site-specific data on groundwater levels, flow directions, connectivity with surface water and water quality.

## Section 7. Key Environmental Factors

### 7.3.2.1 Rustlers Roost

Aquifers beneath the Rustlers Roost lease are associated with fracturing/structural permeability within the metasediments of the South Alligator Group and Burrell Creek Formation (Appendix H). These aquifers are mapped at a local scale (Tickell 2019). Regional data suggests typical bore yields in the Mount Bonnie Formation range from 0.5 – 2 L/s away from major structural features and 0.5 – 5 L/s along major faults or shear zones (Valdora 1994).

A potentiometric surface developed using surveyed water levels in mineral holes pre-mining in 1993, indicates the regional groundwater flow direction is towards the east/north-east and the Mary River with the local flow directions following the natural surface gradient (Valdora 1994). The aquifer response from a short-term (26 hour) pumping test completed prior to mining (Valdora 1994) showed, confined to semi- confined conditions with a transmissivity range of 71 – 107 m<sup>2</sup>/day and a storativity range of  $2 \times 10^{-3}$  –  $10^{-5}$ . Further investigations at the Rustlers Roost site reported a hydraulic conductivity range from 0.8 – 12.5 m/day with a geometric mean of 4.1 m/day (Appendix H).

NR Maps indicate that seven registered bores were drilled along the eastern boundary of ML 1083 for Valdora Mining during 1994. A bore search undertaken during 2016 could not locate any of the historical registered bores. Bore completion depths ranged from 61 to 86 m; SWL ranged between 11 to 23 metres below ground level (mBGL) and yield ranged from 1.5 L/s to 20 L/s. Desktop assessment of the groundwater by CDM Smith (2019b) identified one existing groundwater sampling point (MB1), located downstream of the heap leach pad. The MB1 bore is not a registered bore and there is no bore development report available. There are no other bores located within 5 km of the Rustlers Roost portion of the Project area.

Available records of groundwater level monitoring conducted between 2020 and early 2021 at Rustlers Roost are summarised in Table 7-22.

**Table 7-22 Rustlers Roost Groundwater Levels**

Bore ID	Lat	Long	Mean RSWL [mAHD]	Max RSWL [mAHD]	Min RSWL [mAHD]
RRMB01	-12.926872	131.500677	54.46	55.25	52.78
RRMB02	-12.928138	131.501481	51.85	53.73	49.95
RRMB03	-12.931479	131.492211	54.48	57.05	52.18
RRMB04	-12.923166	131.487615	55.39	57.51	53.18
RRMB05	-12.918846	131.49531	57.7	59.92	55.71
RRMB06	-12.915522	131.502737	56.48	58.69	54.61
RRMB07	-12.908878	131.498342	57.31	59.76	55.33
RRMB08	-12.903331	131.492669	51.47	54.96	49.4

Groundwater flow direction inferred from observations at Rustlers Roost is consistent with topographic relief indicated that the water table resemble a subdued representation of ground surface elevation.

### 7.3.2.2 Quest 29

Groundwater Enterprises (2020) indicates that there is limited groundwater information available onsite or in the immediate vicinity of the lease. Regional scale mapping suggests aquifers across the lease are local scale systems in fractured and weathered rocks with expected bore yields of 1-3 L/s in the metasediments and <0.75 L/s in the Mount Bundey Granite (Tickell 2019). Higher permeabilities are likely associated with structural deformation within the metasediments/dolerite (Sirocco 1999) and at local scale (Appendix H). Slug testing on site undertaken by Groundwater Enterprises (2020) has shown hydraulic conductivity ranges from 0.3 – 38.8 m/day with geometric mean of 5.2 m/day.

## Section 7. Key Environmental Factors

NR Maps records show four registered bores within the Quest 29 ML were historically drilled for mining purposes. Three of these bores (drilled in 1976) were not located during a bore audit undertaken in 2016. The fourth bore, drilled during 1999 for Sirocco Resources, was located immediately north-west of the existing heap leach ponds, and is monitored as part of the Quest 29 groundwater monitoring program (GWB01). Bore completion depths ranged from 17 to 27 m; SWL is artesian to 10 mBGL and yield ranged from 0.25 L/s to 10 L/s. An unregistered bore (GWB02) located to the south-west of the heap leach ponds is also included in the Quest 29 groundwater monitoring plan.

There are five registered bores within a 5 km radius of the Quest 29 portion of the Project area, all bores are associated with mining activities and are either historical investigation holes or monitoring sites. The closest registered bores not associated with mining is a pastoral bore (RN036401) located 6 km north-east of the lease (Appendix H).

Available records of groundwater level monitoring conducted between 2020 and early 2021 at Rustlers Roost are summarised in Table 7-23.

**Table 7-23 Quest 29 Groundwater Levels**

Bore ID	Lat	Long	Mean RSWL [mAHD]	Max RSWL [mAHD]	Min RSWL [mAHD]
Q29MB01	-12.93731	131.577287	68.91	71.65	66.65
Q29MB02	-12.939042	131.577692	68.9	71.69	66.61
Q29MB03	-12.962217	131.587492	31.93	33.32	30.43
Q29MB04	-12.957727	131.584775	36.06	37.24	34.7
Q29MB05	-12.954557	131.585617	44.38	45.07	43.8
Q29MB06	-12.952175	131.579835	46.14	48.62	44.53
Q29MB07	-12.949718	131.58156	49.09	50.61	47.48
Q29MB08	-12.940141	131.581646	78.97	82.75	76.43
Q29MB09	-12.936416	131.574607	62.81	64.17	61.55

There is no groundwater flow information available, however it is assumed to broadly reflect the topographic gradient and surface flows, flowing towards Charlies Creek in the north and the remainder of the site flowing south.

A number of shallow historic mining pits present at Quest 29 hold water from a combination of rainfall, surface water runoff and potentially groundwater.

### 7.3.2.3 Groundwater Interaction with Existing Mine Pits

Investigation has shown that the existing pit lakes at Rustlers Roost and Quest 29 may act as groundwater sinks or trough flow depending on location and depth of the pit (Appendix H):

- Rustlers Roost pit: Groundwater level observed at nearby RRMB05 (57.7 mAHD<sup>13</sup> on average) and RRMB06 (56.5 mAHD on average) were within one meter of the Rustler Roost pit lake water level (56.9 mAHD), indicating that the gradient between groundwater and surrounding aquifer is small. The behaviour of the pit lake is not clearly defined as a sink and may be behaving as a through flow with the

<sup>13</sup> Reference elevation for calculating the reduced standing water levels (RSWL) of the pits was sourced from the digital elevation model (DEM) with 0.5m uncertainty, assuming the datum point at the ground elevation.

## Section 7. Key Environmental Factors

lake receiving groundwater from the western side (RRMB05) and recharging the aquifer on the eastern side (RRMB06);

- Quest 29 Zamu pit: the lake level (37.5 mAHD) is standing approximately 7 m below Q29MB05 average groundwater level (44.4mAHD) and 1.4 m above Q29MB04 groundwater level (36.1 mAHD) suggesting that the pit lake may act as a through flow lake receiving groundwater from the northern side and losing to groundwater on the southern side. The pit is not bounded, and its catchment is not limited to the pit suggesting a larger runoff contribution than if the pit were bounded and pit catchment limited to the strict pit area;
- Quest 29 Taipan pit: the lake level (39 mAHD) is standing approximately 3 m above groundwater level at Q29MB04 (36.1 mAHD) suggesting that the pit lake is leaking to the groundwater aquifer at least on the north-east side of the pit. The pit lake may possibly be working also as a through flow lake as the higher ground elevation on the southern side may suggest higher groundwater level on this side;
- Quest 29 South Koolpin pit: the lake level (40 mAHD) is standing approximately 4 m above groundwater level at Q29MB04 (36.1 mAHD) suggesting infiltration on the southern end of the pit. Furthermore, higher ground surface elevation on the other sides of the pit also suggest likely groundwater seepage to the pit;
- Quest 29 North Koolpin pit: the lake level (52.50 mAHD) is standing above groundwater level at Q29MB07 (49.1 mAHD) and Q29MB06 (46.1 mAHD), suggesting that the lake is losing to groundwater. However, the location of the pit along a ridge may indicates that groundwater along the ridge may be flowing toward the pit; and
- Quest 20 BHS pit: the lake level (70.5 mAHD) is standing above the monitoring groundwater level at Q29B01 (68.9 mAHD) and Q29B02 (68.9 mAHD) suggesting that the pit lake is recharging the aquifer. The standing water level in the BHS pit may result from rainfall runoff across the catchment as the historical pit is not banded.

### 7.3.2.4 Beneficial Uses

The Mary River groundwater management zone (encompassing the eastern portion of Rustlers Roost and the entirety of Quest 29) has declared 'beneficial uses' under the *Water Act 1992*. The defined beneficial uses are environment, riparian and agriculture.


### 7.3.2.5 Groundwater Users

The nearest identified groundwater users include the Old Mount Bunday Station and quarry, Goanna Park and McKinlay River Station. All of these users are located greater than 5 km in distance from the Project area and therefore their groundwater supplies are unlikely to be affected by the Project activities.

### 7.3.2.6 Groundwater Dependent Ecosystems

There are no recorded GDE's within the Quest 29 Project area. The GDE atlas (BOM 2021) maps a low-moderate potential for terrestrial GDEs at two locations on ephemeral watercourses that drain north of the lease (ML 29783) between 2 km to 3 km downstream from the Project area (Appendix H).

There are no recorded GDE's within the Rustlers Roost Project area. The GDE atlas (BOM 2021) maps a moderate potential for terrestrial GDEs along watercourses that drain north of the Project area. These occur approximately 1 km to 2 km downstream from the Project area (Appendix H).



**Legend**

- Surface Water Beneficial Area
- Ground Water Beneficial Area
- Major Watercourse
- Minor Watercourse
- River Basin
- Project Area

R	Details	Date	©COPYRIGHT CDM SMITH This drawing is confidential and shall only be used for the purpose of this project.			
1	Final	26/08/21	DESIGNED	SS	CHECKED	TK
-	-	-	DRAWN	SS	CHECKED	TK
-	-	-	APPROVED	TK	DATE	26/08/21
Notes:						

<p>0 6,500 13,000 26,000</p> <p>Meters</p> <p>1 cm = 6,407 meters</p> <p>GCS GDA 1994 MGA Zone 52</p>						
---	--	--	--	--	--	--

**DISCLAIMER**  
CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

DATA SOURCE  
NT Government Open Source Data

DESIGNER

CLIENT

**FIGURE 7-22**

**Mary River Groundwater and Surface Water Beneficial Use Areas**

DRG Ref: 1001087-EIS-07-7.22

## Section 7. Key Environmental Factors

### 7.3.3 Potential Impacts and Risks

This section identifies, describes, and assesses the potential impacts and risks to hydrological processes from disruption to the natural alignment of creek lines and drainage features, dewatering and groundwater abstraction to the water table and discharge of surface water from pit dewatering. The environmental risk assessment discussed in Section 6 and presented in Appendix B identified and considered potential sources of impacts to hydrological processes. A summary of the identified sources and the associated potential impacts is presented in Table 7-24.

**Table 7-24 Potential sources of impacts to hydrological processes**

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
HP-1	Vegetation clearing for the Project	Construction Operation	<p><b>Direct</b> - Disturbing an additional 333.4 ha of land for the Rustlers Roost, 26.16 ha for Quest 29, 7.3 ha for the accommodation camp and 2 ha for the haul road. Loss of 368.86 ha of habitat. Resulting in potential decreased infiltration during precipitation, increased runoff (quantities and velocities) resulting alterations to drainage line (including scouring and incising).</p> <p>Disruption to the natural alignment of creeks and streams reducing or presenting flows downstream.</p> <p><b>Indirect or Cumulative</b> - Increased disturbance and lost productivity of surface water features in the wider Mount Bunday locality coupled with disturbance at Toms Gully Mine and the nearby Mount Bunday Training Area. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation.</p>
HP-2	Overtopping, embankment failure or seepage from the new TSF at Rustlers Roost leading to uncontrolled release of tailings material to surrounding environment.	Construction, Operation, Decommissioning or Closure	<p><b>Direct</b> - Direct alteration of the hydrological regime including potential influx that causes significant destruction to existing drainage lines on and off site. Potential for persistent alteration of the local groundwater regime through seepage and mounding. Potential alteration of the water table that would impact features of the natural environment that are reliant on existing conditions (e.g. GDEs).</p> <p>Impact on structural integrity of engineered embankments threatening additional failures and contaminant releases (e.g. adjacent decommissioned heap leach pad).</p> <p>Groundwater interaction with contaminants from TSF seepage.</p> <p><b>Indirect or Cumulative</b> - Contribution of overtopping flows of embankment failures to discharges from Toms Gully Mine into the Mount Bunday catchment resulting in increased water levels, flooding of area typically not susceptible to inundation, higher watercourse velocities, scouring and downstream deposition. Negative implications on the riparian environment and capacity to naturally accommodate wet season events.</p>
HP-3	Overtopping, embankment failure or seepage from the process water storage at Rustlers Roost	Operation, Decommissioning and Closure	<p><b>Direct</b> - Direct alteration of the hydrological regime including potential influx that causes significant destruction to existing drainage lines on and off site. Potential for persistent alteration of the local groundwater regime through seepage and mounding. Potential alteration of the water table that would impact features of the natural</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
	leading to uncontrolled release of process water to surrounding environment.		<p>environment that are reliant on existing conditions (e.g. GDEs).</p> <p>Impact on structural integrity of engineered embankments threatening additional failures and contaminant releases (e.g. adjacent decommissioned heap leach pad).</p> <p>Groundwater interaction with contaminants from process water storage dam.</p> <p><b>Indirect or Cumulative</b> - Contribution of overtopping flows of embankment failures to discharges from Toms Gully Mine into the Mount Bundey catchment resulting in increased water levels, flooding of area typically not susceptible to inundation, higher watercourse velocities, scouring and downstream deposition. Negative implications on the riparian environment and capacity to naturally accommodate wet season events.</p>
HP-4	Embankment failure or seepages from the new WRDs at Rustlers Roost and Quest 29 to surrounding environment.	Operation, Decommissioning and Closure	<p><b>Direct</b> - Direct alteration of the hydrological regime including potential influx that causes significant destruction to existing drainage lines on and off site. Potential for persistent alteration of the local groundwater regime through seepage and mounding. Potential alteration of the water table that would impact features of the natural environment that are reliant on existing conditions (e.g. GDEs).</p> <p>Impact on structural integrity of engineered embankments threatening additional failures and contaminant releases (e.g. adjacent decommissioned heap leach pad).</p> <p>Groundwater interaction with contaminants from WRDs.</p> <p><b>Indirect or Cumulative</b> - Contribution of overtopping flows of embankment failures to discharges from Toms Gully Mine into the Mount Bundey catchment resulting in increased water levels, flooding of area typically not susceptible to inundation, higher watercourse velocities, scouring and downstream deposition. Negative implications on the riparian environment and capacity to naturally accommodate wet season events.</p>
HP-5	Embankment failure of Annie's Dam water storage or process water ponds and uncontrolled water and sediment release.	Construction, Operation	<p><b>Direct</b> - Adverse impacts to Marrakai Creek including potential influx surface water that causes significant destruction to existing drainage lines on and off site. Direct disturbance of the hydrological regime of Marrakai Creek and alteration of the riparian environment. Localised severe scouring of the topsoils in the area surrounding the breach and exposure of subsoils to erosive factors which could lead to further impact to surface water features. Impact on structural integrity of engineered embankments.</p> <p><b>Indirect or Cumulative</b> - Addition of affected drainage lines to the Adelaide River catchment contributing to minor but cumulative catchment runoff, higher watercourse velocities, scouring and downstream deposition. Potential contribution to the formation of anthropogenic induced depositions, damming and backflow lagoons downstream. This could result in inundation of areas not previously subject to flooding and thus alteration of ecological conditions in those areas.</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
HP-6	Groundwater drawdown.	Construction, Operation	<p><b>Direct</b> - Reduced water table elevation due to dewatering has the potential to reduce access to groundwater by riparian vegetation (including GDEs). Impact to any groundwater dependent ecosystems including aquatic ecosystems that are dependent on groundwater to provide dry season refuge. Potential change to surface water quality due to dewatering activity.</p> <p><b>Indirect and Cumulative</b> - Cumulative drawdown of groundwater across three relatively close sites (Rustlers Roost, Quest 29 and Toms Gully) resulting in drawdown across the upper Mount Bunday Creek catchment. Potential to impact any localised GDE species and recharge of the local tributaries. Cumulative impacts could also occur with drawdown associated with nearby quarries.</p> <p>Potential increase in cumulative impact on groundwater level in conjunction with Toms Gully Mine and nearby quarries.</p>
HP-7	Indiscriminate use of existing waste rock for construction. Storage of waste rock outside of pit footprint for too long.	Construction Operation Decommissioning Closure	<p><b>Direct</b> - Diversion of existing runoff pathways, whether this be overland flow within drainage lines. This would likely result in scouring and incision causing altered flow paths leading to loss of topsoil, sedimentation of waterways and altered upper-catchment hydrological regime. This would adversely affect the biological processes that depend on water quality.</p> <p>Groundwater interaction with contaminants from incorrect storage of waste rock.</p> <p><b>Indirect or Cumulative</b> - Increased disturbance and lost productivity of surface water features in the wider Mount Bunday locality coupled with disturbance at Toms Gully Mine and the nearby Mount Bunday Training Area. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation. Indirect biological and human health implications in the immediate location of the placement and areas subject to seepage or runoff.</p>
HP-8	Pit and groundwater dewatering exposing PAF and causing AMD.	Construction Operation Decommissioning Closure	<p><b>Direct</b> - Reduction of onsite water quality and potential exceedance of SSTVs, if discharged. Adverse impacts on downstream water quality, aquatic environment, and downstream users.</p> <p>Groundwater interaction with PAF.</p> <p><b>Indirect and Cumulative</b> - Potential transportation of PAF material, with potential to cause contamination, throughout the Project area and external. With specific relevance to hydrological processes this would have the potential to lead to dieback of riparian vegetation exposing sediments, reducing infiltration and waterway roughening, thus resulting in higher instream velocities, scouring and downstream sedimentation. Indirect biological and human health implications in the immediate location of the PAF material and areas subject to seepage or runoff.</p>
HP-9	Planned pit over topping or release to surface water	Construction Operation	<p><b>Direct</b> - Contamination of surrounding water features and alteration of water characteristics, including chemical, physical, biological and aesthetic qualities. Adversely</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
	features during extreme rainfall and flooding events.		<p>affecting the biological processes that depend on water quality (pyrite, pyrrhotite and arsenopyrite are expected to be present in tailings in quantities that will be Potentially Acid Forming).</p> <p><b>Indirect and Cumulative</b> - Potential transportation of contaminated sediments and material throughout the Project area and external. Biological and human health implications (primary contaminant of concern being cyanide). Contamination of downstream environments resulting in human health risks that would necessitate the closure of watercourse to extraction of drinking water, recreation, and fishing.</p>
HP-10	Unplanned pit overtopping or release to surface water features during extreme rainfall and flooding events.	Construction Operation Decommissioning Closure	<p><b>Direct</b> - Direct alteration of the hydrological regime including potential influx that causes significant destruction to existing drainage lines on and off site. Potential for persistent alteration of the local groundwater regime through seepage and mounding. Potential alteration of the water table that would impact features of the natural environment that are reliant on existing conditions (e.g. GDEs).</p> <p>Impact on structural integrity of engineered embankments threatening additional failures and contaminant releases (e.g. adjacent decommissioned heap leach pad).</p> <p><b>Indirect or Cumulative</b> - Contribution of overtopping flows of embankment failures to discharges from Toms Gully Mine into the Mount Bunday catchment resulting in increased water levels, flooding of area typically not susceptible to inundation, higher watercourse velocities, scouring and downstream deposition. Negative implications on the riparian environment and capacity to naturally accommodate wet season events.</p>
HP-11	Erosion of site infrastructure leading to sedimentation	Operation, Decommissioning Closure	<p><b>Direct</b> - Potential direct alteration of flow paths onsite and decreased structural integrity of the impacted infrastructure. Movement of soil or rock material from site infrastructure (e.g. WRD or TSF embankments) contributing to sedimentation and blockage of natural drainage lines leading to localised flooding and erosion.</p> <p><b>Indirect or Cumulative</b> - Contribution to exposed ground in the Project area and general locality. Thus, contributions to the surface water runoff in the wider area.</p>
HP-12	Release of hazardous chemicals or materials during storage and handling onsite.	Construction, Operation, Decommissioning	<p><b>Direct</b> - Contamination of surface water and groundwater and alteration of water characteristics, including chemical, physical, biological and aesthetic qualities. Adversely affecting the riparian flora if the contaminants reach drainage lines and leading to vegetation dieback.</p> <p><b>Indirect or Cumulative</b> - Potential transportation of contaminated sediments and material throughout the Project area and external. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation.</p>
HP-13	Poor handling and management of	Operation, Decommissioning	<p><b>Direct</b> - Diversion of existing runoff pathways, whether this be overland flow within drainage lines. This would likely result in scouring and incision causing altered flow paths</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
	tailings and waste rock		<p>leading to loss of topsoil, sedimentation of waterways and altered upper-catchment hydrological regime. This would adversely affect the biological processes that depend on water quality.</p> <p>Potential alteration of flow paths resulting in decreased structural integrity of the impacted infrastructure. Movement of soil or rock material from site infrastructure (e.g. WRD or TSF embankments) contributing to sedimentation and blockage of natural drainage lines leading to localised flooding and erosion.</p> <p>Groundwater interaction with contaminants from tailings and waste rock.</p> <p><b>Indirect or Cumulative</b> - Increased disturbance and lost productivity of surface water features in the wider Mount Bunday locality coupled with disturbance at Toms Gully Mine and the nearby Mount Bunday Training Area. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation. Indirect biological and human health implications in the immediate location of the placement and areas subject to seepage or runoff.</p>
HP-14	Production of domestic waste and storage of the waste onsite	Construction, Operation, Decommissioning.	<p><b>Direct</b> - Contamination of surface water and groundwater in the area proximal to the domestic waste receptacle where inappropriate storage vessels and management is used. Alteration of water characteristics, including chemical, physical, biological and aesthetic qualities resulting in riparian or GDE impacts that impact hydrological processes (e.g. dieback of vegetation and increase scouring).</p> <p><b>Indirect or Cumulative</b> - Potential transportation of contaminated sediments and material throughout the Project area and external. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation.</p>
HP-15	Unfinished/ unsuccessful rehabilitation of Project due to inadequate funds or natural disaster (e.g. cyclone).	Construction, Operation, Decommissioning and Closure	<p><b>Direct</b> - Site not rehabilitated to required standards. Increased potential for offsite impacts from AMD, erosion and sedimentation. Degradation of water quality onsite and various forms of erosion (sheet, rill, wind etc.) transporting soils into water features, potentially resulting in sedimentation and backflows (afflux).</p> <p><b>Indirect or Cumulative</b> - Potential transportation of contaminated sediments and material throughout the Project area and external. Biological and human health implications (primary contaminant of concern being cyanide). Contamination of downstream environments resulting in human health risks that would necessitate the closure of watercourse to extraction of drinking water, recreation and fishing.</p> <p>Given PGO is the same proponent for the nearby Toms Gully Mine project it would likely result in unfinished or unsuccessful rehabilitation at both sites. This would result in a large area of disturbed and unrehabilitated land in the Mount Bunday catchment cumulatively resulting in</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
			increased sediment loads to Mount Bunday Creek and the downstream Mary River.
HP-16	Long term positive water balance	Construction, Operation, Decommissioning and Closure	<p><b>Direct</b> - Potential build-up of water onsite and the need for long term treatment and constant discharges of water. Positive water balance could potentially mean surrounding areas (groundwater and surface water) are not receiving typical supply. This has potential to influence an imbalance of the local hydrological regime which could adversely impact ecological features such as GDEs.</p> <p><b>Indirect and Cumulative</b> - Likely result in a constant requirement for ongoing discharges and a regular pulses of site water into the environment rather than a steadier flow that would occur in a natural system. This could indirectly result in scouring and degradation of drainage features that receive the discharged water.</p>
HP-17	Inappropriate management of the decommissioned site, post closure landform.	Closure	<p><b>Direct</b> - Unauthorised access to the site by externals (including public, leaseholders and livestock) negatively affecting rehabilitation potential and contributing to rehabilitation failure. Potential scouring, soil erosion, loss of topsoil and sedimentation resulting in the alteration of on and off site drainage features.</p> <p><b>Indirect or Cumulative</b> - Increased disturbance of soils in the wider Mount Bunday locality coupled with disturbance at Toms Gully Mine and the nearby Mount Bunday Training Area, resulting in altered hydrological regime (primarily surface water) to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation.</p>
HP-18	Ineffective operational implementation of site environmental management system, plans and procedures.	Construction, Operation, Decommissioning Closure	<p><b>Direct</b> - Contamination of surface water and groundwater and alteration of water characteristics, including chemical, physical, biological and aesthetic qualities. Adversely affecting the riparian flora if the contaminants reach drainage lines and leading to vegetation dieback and scouring of surface water features.</p> <p><b>Indirect or Cumulative</b> - Rehabilitation success is affected by inappropriate operational procedures which results in decreased likelihood of achieving rehabilitation goals and closure requirements following decommissioning. Agreed PMLU cannot be achieved due to significant environmental incidents resulting in widespread ongoing contamination of water features.</p> <p>Potential increase in cumulative concentration of sediments within the downstream watercourse as a result of any sediment discharged. Increased downstream depositions and siltation impacts.</p>
HP-19	Inappropriate liquid and solid waste disposal.	Construction, Operation, Decommissioning Closure	<p><b>Direct</b> - Contamination of surface water and groundwater and alteration of water characteristics, including chemical, physical, biological and aesthetic qualities. Adversely affecting the riparian flora if the contaminants reach drainage lines and leading to vegetation dieback and scouring of surface water features.</p> <p><b>Indirect or Cumulative</b> - Rehabilitation success is affected by inappropriate operational procedures which results in decreased likelihood of achieving rehabilitation goals and closure requirements following decommissioning. Agreed</p>

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Summary of Potential Impacts
			<p>PMLU cannot be achieved due to significant environmental incidents resulting in widespread ongoing contamination of water features.</p> <p>Potential increase in cumulative concentration of sediments within the downstream watercourse as a result of any sediment discharged. Increased downstream depositions and siltation impacts.</p>
HP-20	As part of closure and rehabilitation, creeks and drainage alignments are not consistent to the surrounding landforms and catchment area.	Closure	<p><b>Direct</b> - Diversion of existing runoff pathways, whether this be overland flow within drainage lines. This would likely result in scouring and incision causing altered flow paths leading to loss of topsoil, sedimentation of waterways and altered upper-catchment hydrological regime. This would adversely affect the biological processes that depend on water quality.</p> <p><b>Indirect or Cumulative</b> - Increased disturbance and lost productivity of surface water features in the wider Mount Bunday locality coupled with disturbance at Toms Gully Mine and the nearby Mount Bunday Training Area. Resulting in reduced local capacity of surface water features to perform ecological functions and a cumulative increase in erosion contributing to waterway sedimentation. Indirect biological and human health implications in the immediate location of the placement and areas subject to seepage or runoff.</p>

The following sections provide a summary of the potential key impacts on hydrological processes and considers the severity and extent of these impacts and implications for protection of environmental values.

### 7.3.3.1 Alteration of Surface Flow

To analyse environmental flows for all associated catchments under a post mining scenario, simulations were conducted under the following assumptions (Primary Gold 2021a, Primary Gold 2021b):

- Baseline condition as the site is represented today, using 100-year rainfall records from 1921 to 2021;
- Undisturbed condition for the future 100 year, used the same rainfall record with the climate change scenario applied to simulate the next 100 years; and
- Post-mining Hydrologic Modelling System (HEC-HMS) model with rainfalls as outlined in the second point to assess changes occurring to total flow and peak flow resulting from changed catchment conditions resulting from mining.

A summary of the modelled Project induced changes to surface flows are discussed in the following sub-sections.

#### Rustlers Roost East (Mount Bunday Creek)

Overall the simulation showed a decline of mean annual flow by 0.5 ML (10%) and decline of peak flow by  $1.3 \text{ m}^3\text{s}^{-1}$  (6.6%) under the climate change scenario in the post-mining landform. These losses are mainly due to refilling the pit over several decades post mining. While the TSF increases the post-mining catchment area, the modelled elevations have shown that the water level will not reach a spillway level that may contribute to downstream flows.

## Section 7. Key Environmental Factors

### Rustlers Roost west (Marrakai Creek)

The simulated post-mining flow for the Marrakai Creek catchment has shown a decline of mean annual flow by 0.5 ML (38%) and decline of peak flow by 1.81 m<sup>3</sup>s<sup>-1</sup> (34%). As the modelled Marrakai Creek catchment domain is small and in the headwaters of the very large Adelaide River catchment, it is unlikely that these reductions will have an adverse impact on environmental flows further downstream.

### Quest 29 north (Mount Bunday Creek)

The model has shown little difference for the mean annual flow and peak flow with a decline by 0.02 ML (1%) and decline by 0.08 m<sup>3</sup>s<sup>-1</sup> (1%), respectively. The small reduction has been attributed to the change of catchment size post-mine closure where the rehabilitated heap leach pad potentially drains into the Quest 29 south catchment.

### Quest 29 South (McKinlay River)

The simulation for Quest 29 south showed a small decline of mean annual flow by 0.06 ML (1%) and rise in peak flow by 0.6 m<sup>3</sup>s<sup>-1</sup> (11%), potentially associated with the projected climate change.

Based on the hydrological analysis, the Rustlers Roost and Quest 29 sites are not likely to significantly impact surface water flows downstream in Mount Bunday Creek, Marrakai Creek or McKinlay River. This is because the Project area is located in the headwaters of upper catchment areas, where surface water inputs from the minor ephemeral drainage lines (stream one order) contribute a very small portion of the overall catchment flows. At Rustlers Roost, the proposed TSF footprint intersects a minor drainage line within the upper Mount Bunday Creek catchment and Annie's Dam intersects a minor drainage line within the upper Marrakai Creek catchment. At Quest 29, the most southern pits are sited over two minor drainage lines in the McKinlay River catchment.

Localised alteration of flows to the ephemeral drainage lines will occur associated with developing new mine infrastructure, dewatering of existing pit lakes and expansion of existing pits. Some of the direct rainfall into the Project area that under natural conditions would either seep into the ground or runoff into drainage lines, will be retained in pits or other structures on site, whilst 'clean' stormwater will be captured in sediment basins and discharged. This will result in reduced runoff occurring within the immediate sub-catchment and is not expected to have an impact on surface flows in the creeks and rivers downstream to the extent of impacting ecological functioning.

The water balance model has shown that excess water produced at Rustlers Roost Project area requires disposal during operation at a maximum dewatering rate of 950 l/s or a total of 30,000 ML and 420 l/s or a total of 6,000 ML for Quest 29 by the end of mining. Nearly 80% of the water required to be discharged will come from groundwater seepage, with the remaining 20% from direct rainfall into the pit and runoff from the pit faces. However, the water balance model had a high level of uncertainty regarding the actual dewatering volume, due to data paucity that would allow to infer hydraulic conductivity of the aquifers in the vicinity of the Project area. Previous field testing (aquifer slug tests) undertaken at the site resulted in a large range of values representing a few orders of magnitudes and there was also lack of data to support calibrating the model to constrain these values (Appendix H).

Discharge of excess water to Mount Bunday Creek from pit dewatering is not likely to be consequential due to the downstream Mary River Floodplain receiving large volumes of water during the wet season. The surface hydrological model for the Quest 29 catchment has shown a mean baseline environmental flow of 1,640 l/s for Mount Bunday Creek and 5,000 l/s for the McKinlay River tributary (Table 7-21). In contrast, the water balance model (Appendix H) has shown a maximum discharge rate from all pits at a maximum of 410 l/s, with a projected discharge rate well below 100 l/s for most of the time.

## Section 7. Key Environmental Factors

In summary, the analysis indicated that mining and the planned water management during dewatering will have little impact on downstream environmental flows. Information on discharge volumes from pit-dewatering is provided in the WMP (Appendix I). The water released will be a combination of intercepted surface flows, rainfall and groundwater dewatered from the open pits to allow for mining in accordance with the WDL.

### 7.3.3.2 Flooding



Positioned in the upper headwaters, the sites are unlikely to be impacted by flooding. Surface water flow is expected to peak and subside rapidly after rainfall events.

Flooding analysis by CDM Smith (2019a) found that (with the existing infrastructure) the Rustlers Roost site is unlikely to be affected by flooding, with the undisturbed sections largely free draining, and the disturbed sections draining mostly to the pit.

Flooding modelling developed by GHD (2019) for existing site infrastructure at Quest 29 concluded:

- The BHS pit, South Koolpin and North Koolpin pits are likely to be unaffected by flood inflow from the adjacent creeks for events up to and including the probable maximum flood (PMF) event;
- The heap leach pad and leach ponds are also unaffected by external flooding for events up to the 0.1% Annual Exceedance Probability (AEP) flood event;
- The Taipan pit and Zamu pit are flooded from external sources for all the events analysed, having been constructed on a drainage line; and
- Flow velocities are generally low around the pits, except at those locations where the pits are overtopped.

An additional hydrology and flood modelling assessment was completed to inform this Draft EIS (Appendix N). The modelling indicates that from a flood risk assessment standpoint, for a 1% AEP event there are flood risks, but these are not widespread (refer to Figure 7-23 and Figure 7-24). For a PMF scenario, there is a high risk in nearly every channel and around the Taipan pit, however appropriate post-mine safety bunding to 2 m is expected to ameliorate this. For the Rustlers Roost portion of the Project area there is little risk to humans due to direct rainfall and runoff from the mine site as access to the site is restricted and not open to the public. The broader area of the mine site is entered from the Arnhem Highway through fenced private property and through the quarry at Mount Bunday. All remaining water bodies will be bunded.



## Section 7. Key Environmental Factors

### 7.3.3.3 Drawdown of Groundwater Aquifers

A numerical groundwater model was developed to estimate the potential maximum drawdown induced by mining the pits at Rustlers Roost and Quest 29, and the potential groundwater inflows to the proposed mining pits. The model boundary in the regional setting is presented in Figure 7-25 and the model grid is shown in Figure 7-26. Refer to Appendix H for details of the model setup.

Dewatering of the mine pits during operations and extraction of groundwater as a water supply, has potential to drawdown the water levels in the groundwater aquifer. Typically, these types of activities can create a drawdown cone of depression that alters groundwater flows and lowers groundwater levels for some distance around the open pits and bores. Groundwater modelling has shown that the calculated 1 m drawdown from the pit dewatering may extend 5 km to the north and 3 km to the south of the Rustlers Roost pits, and 2 km to the south-west of the Quest 29 pits (Figure 7-27). The modelling also suggests that the probability of Marrakai Creek, Mary River and McKinlay River being impacted by drawdown from the mining is minimal (Appendix H).

Groundwater drawdown associated with the mining activities is unlikely to impact any other groundwater users as the closest user is over 5 km from the Project area, and therefore outside the modelled 1 m drawdown area. Desktop studies have not identified any GDE's in proximity to the site that would be affected by groundwater drawdown. As the level of connection between groundwater and surface water flows in the area is not yet determined, the extent to which any drawdown would impact surface water flows in ephemeral drainage lines is uncertain.


Groundwater recovery post-mining will be verified by groundwater modelling. Historic survey data of the pit shell was derived at the cessation of mining in 1997 and survey level data (mRL) sourced from a computer-aided design (CAD) file, and climate (rainfall and evaporation) data sourced from SILO data was used to develop a pit lake storage curve and pit surface area curve. The data shows, from an empty pit shell in 1997, a steep increase in water level (15 m over the initial 3-4 years), contributed to limited surface area for evaporation. A more gradual increase in water volume occurred with a larger pit lake surface area, reaching a dynamic equilibrium between 56 m AHD (3 GL) and 62 m AHD (4.5 GL). In addition, CDM Smith (2019b) determined that the pit lake acts as a hydraulic sink for a large portion of the disturbed catchment, meaning that the pit lake water evaporates faster than the influx of water (rainfall, runoff and groundwater ingress).

The plan to install investigative and monitoring bores, as well as utilising existing bores on the site will allow for continued refinement of the groundwater model. Continued refinement of the model will improve confidence in the extent and depth of drawdown, sustainable levels of extraction from bores, expected rates of groundwater recovery and surface-groundwater connections.

A site water balance model was developed to estimate the viability of the proposed WMP in its ability to prevent uncontrolled spills to the environment and to keep a dry working environment during mining phases and to evaluate the likelihood of overflowing of the pit lakes (Appendix H).

The output of the water balance model indicates that groundwater seepage is the biggest contributor to the water balance amounting to ~83% of all inflows. While there is a notable amount of uncertainty regarding the degree of groundwater inflow to be managed (i.e. 100 L/s to 600 L/s), monitoring of pit seepage during the initial phase of operation will significantly reduce this uncertainty. Water is planned to be released from the mine site and directed to Mounty Bunday or Marrakai Creeks at times when it cannot be stored or utilised onsite. Over the LOM, it is estimated that around 65 GL of water may be released between 2022 and 2031, which is well within the limits of environmental water flows for these water bodies.

Potential impacts from surface and groundwater contamination have been addressed in Section 7.4– Inland Water Environmental Quality.




**Legend**

- Model Domain Area
- Watercourse Intersecting Project Area
- Major Watercourse
- Minor Watercourse
- Stream
- Subcatchment
- Pastoral Property
- Directory of Important Wetlands
- Sites of Conservation Significance
- Accomodation Camp
- Project Area

R	Details	Date
1	Final	25/08/21
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

©COPYRIGHT CDM SMITH This drawing is confidential and shall only be used for the purpose of this project.				
DESIGNED	SS	CHECKED	TK	
DRAWN	SS	CHECKED	TK	
APPROVED	TK	DATE	25/08/21	
Notes:				



**DISCLAIMER**  
CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

DATA SOURCE  
NT Government Open Source Data


DESIGNER

CLIENT

FIGURE 7-25

**Regional Site Map and Groundwater Model Domain**

DRG Ref: 1001087-WATERBAL-1.5



**Legend**

- River
- GHB
- Drain
- Grid
- Project Area

R	Details	Date
1	Final	24/08/21
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

©COPYRIGHT CDM SMITH  
This drawing is confidential and shall only be used for the purpose of this project.

DESIGNED	SS	CHECKED	TK
DRAWN	SS	CHECKED	TK
APPROVED	TK	DATE	24/08/21

Notes:

N

0    1,200    2,400    4,800

Meters  
1 cm = 1,112 meters  
GCS GDA 1994 MGA Zone 52

**DISCLAIMER**  
CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

DATA SOURCE  
NT Government Open Source Data


DESIGNER

CLIENT

FIGURE 7-26

**Groundwater Model Grid and Boundary Conditions**


DRG Ref: 1001087-WATERBAL-1.7



- Legend**
- Rustlers Roost and Quest 29 - 1m Drawdown Outer Extent
  - Rustlers Roost - 1m Drawdown High Confidence Extent
  - Quest 29 - 1m Drawdown High Confidence Extent
  - Proposed Pit
  - Major Watercourse
  - Minor Watercourse
  - Stream
  - Project Area

R	Details	Date
1	Final	07/09/21
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

©COPYRIGHT CDM SMITH This drawing is confidential and shall only be used for the purpose of this project.			
DESIGNED	SS	CHECKED	TK
DRAWN	SS	CHECKED	TK
APPROVED	TK	DATE	07/09/21
Notes:			



**DISCLAIMER**  
 CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

**DATA SOURCE**  
 NT Government Open Source Data



FIGURE 7-27

**Groundwater Model Predicted Extents**

DRG Ref: 1001087-EIS-07-7.27

## Section 7. Key Environmental Factors

### 7.3.3.4 Cumulative Impact

There are four active extractive industry operations and one approved, but not yet active, mining operation in proximity to the Project area. The construction and operation of the Project has the potential to incrementally alter environmental flows in a cumulative context with adjacent hydrologically connected projects.

To address the ToR requirement for this Draft EIS, an assessment of the cumulative impacts of the Project across four spatial scales has been conducted. The spatial scales of consideration are:


- Property – defined as Mount Bunday Station and McKinlay River Station;
- Catchment – defined as the Mount Bunday Creek catchment, Marrakai Creek catchment and McKinlay River catchment;
- Region – defined as the Marrakai-Douglas Daly unincorporated area; and
- Bioregion – defined as the Pine Creek bioregion.

The cumulative impact assessment has considered the effects of multiple actions or impacts on hydrological process (surface water and groundwater) (refer Table 7-18)

Cumulative discharges from the Project area and the downstream Toms Gully Mine are unlikely to impact the hydrological processes as discharges will be proportional to flows occurring in the Mount Bunday Creek Catchment. Mount Bunday Creek is a higher stream order, has intact riparian vegetation and is able to withstand high flows throughout the wet season, and it is anticipated very little erosion beyond natural occurrence will occur (Aquatic Ecology Services 2019).

As part of the Toms Gully Mine EIS, potential groundwater inflow into that project decline access was modelled. The modelling found that the cone of depression is mainly contained in the Toms Gully Mine tenements and it is therefore unlikely that mine dewatering would affect bores outside the mining tenements or have a cumulative drawdown interaction with the Project. The Old Mount Bunday homestead bore RN027956 is the bore most at risk of being affected by dewatering from the Toms Gully Mine and that bore is outside the area of influence for the drawdown related to this Project (refer to Figure 7-28).

Furthermore, the groundwater model for this Project predicts the cone of depression induced by the proposed groundwater extraction may extend up to 5 km to the north and 3 km to the south of the Rustlers Roost pits and 2 km to the south-west of the Quest 29 pits. There is only a minor potential area of overlap in the modelled maximum extents of influence between the Project and Toms Gully Mine (refer to Figure 7-28). Therefore, the likelihood of cumulative groundwater interactions with Toms Gully Mine is considered low.




- Legend**
- Rustlers Roost and Quest 29 - 1m Drawdown Outer Extent
  - Rustlers Roost - 1m Drawdown High Confidence Extent
  - Quest 29 - 1m Drawdown High Confidence Extent
  - Toms Gully Groundwater Model Extent
  - Permanent Surface Water Feature
  - Proposed Pit
  - Major Watercourse
  - Minor Watercourse
  - Stream
  - Project Area

R	Details	Date	©COPYRIGHT CDM SMITH This drawing is confidential and shall only be used for the purpose of this project.			
1	Final	07/09/21	DESIGNED	SS	CHECKED	TK
-	-	-	DRAWN	SS	CHECKED	TK
-	-	-	APPROVED	TK	DATE	07/09/21
Notes:						

0 1,500 3,000 6,000 Meters 1 cm = 1,386 meters GCS GDA 1994 MGA Zone 52						
--	--	--	--	--	--	--

DISCLAIMER  
 CDM Smith has endeavoured to ensure accuracy and completeness of the data. CDM Smith assumes no legal liability or responsibility for any decisions or actions resulting from the information contained within this map.

DATA SOURCE  
 NT Government Open Source Data



CLIENT

FIGURE 7-28  
**Cumulative Groundwater Drawdown Extents**  
 DRG Ref: 1001087-EIS-07-7.28

## Section 7. Key Environmental Factors

**Table 7-25 Assessment of Cumulative Impacts to Hydrological Processes**

Project	Spatial Extent				Approx. Distance from Project	Impact Details	Reference
	Property	Catchment	Region	Bioregion			
Toms Gully Mine	✓	✓	✓	✓	0 km	Approximately 76 ha of disturbance. Altered surface and water flow regimes. Groundwater drawdown from pit dewatering activities interaction is limited minor extent shown in Figure 7-28.	NT EPA 2020a
Boral Quarry	✓	✓	✓	✓	700 m	Approximately 35 ha of disturbance (including access road of 2.5 ha) Altered surface and water flow regimes. Groundwater drawdown from pit dewatering activities.	NR Maps spatial mapping (DEPWS 2021)
HB Quarry	✓	✓	✓	✓	2 km	Approximately 47.5 ha of disturbance. Altered surface and water flow regimes. Groundwater drawdown from pit dewatering activities.	NR Maps spatial mapping tool (DEPWS 2021)
McKinlay Quarry	✓	✓	✓	✓	3.5 km	Approximately 17.5 ha of disturbance (including access road of 3 km) Altered surface and water flow regimes. Groundwater drawdown from pit dewatering activities.	NR Maps spatial mapping tool (DEPWS 2021)
Ostojic Quarry	✓	✓	✓	✓	4.4 km	Approximately 47.5 ha of disturbance. Altered surface and water flow regimes. Groundwater drawdown from pit dewatering activities.	NR Maps spatial mapping tool (DEPWS 2021)
Mount Bunday Military Training Area			✓	✓	9 km	The Mount Bunday Training Area is a 117,300 ha. No publicly available data No more than 10 ha of disturbance.	NR Maps spatial mapping tool (DEPWS 2021)
Woolwonga Mine				✓	47 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021)
Hayes Creek Mine				✓	58 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) LES 2017
Union Reefs Gold Mine				✓	60 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) NT EPA 2020b

## Section 7. Key Environmental Factors

Project	Spatial Extent			Bioregion	Approx. Distance from Project	Impact Details	Reference
	Property	Catchment	Region				
Frances Creek Iron Ore Mine				✓	75 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) MBS Environmental 2006
Finnis Lithium Mine					80 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) EcOz 2020
Fountain Head Gold Mine				✓	90 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) ERIAS 2021
Jabiru Hybrid Power Station				✓	140 km	Unlikely cumulative impacts on hydrological processes, due to distance and different sub-catchment.	NR Maps spatial mapping tool (DEPWS 2021) CDM Smith 2021

## Section 7. Key Environmental Factors

### 7.3.4 Avoidance, Mitigation and Management

Avoidance, mitigation and management measures for hydrological processes are presented in Table 7-26.

**Table 7-26 Avoidance, Mitigation and Management Measures for Hydrological Processes**

Potential Consequences	Measures
Alteration of drainage lines, disruption of natural alignment of creeks and streams	<p><b>Avoid</b></p> <ul style="list-style-type: none"> <li>▪ Only clearing the practical minimum footprint necessary for the portion of the Project to be implemented</li> <li>▪ Clearly mark limits of clearing</li> <li>▪ Make use of already disturbed areas where possible</li> <li>▪ Adhere to buffer widths recommended by the Northern Territory Land Clearing Guidelines with regard to riparian vegetation in drainage lines</li> <li>▪ Avoid land clearing during the December to March portion of the wet season.</li> </ul> <p><b>Mitigation and Management</b></p> <ul style="list-style-type: none"> <li>▪ Adherence to Ground Disturbance Procedures</li> <li>▪ Implement erosion and sediment controls in accordance with an ESCP</li> <li>▪ Implementation of Biodiversity Management Plan</li> <li>▪ TSF to be planned, designed, constructed and operated in accordance with approaches details in the guideline Tailings Management: Leading Practice Sustainable Development Program for the Mining Industry (Australian Government 2016a)</li> <li>▪ Design TSF to contain a range of design storm and rainfall sequences events up to and greater than the required design criteria</li> <li>▪ An operational emergency spillway to be constructed as part of each embankment raise</li> <li>▪ Development of Monitoring Plan / Operational Manual which includes weekly inspections of the TSF, survey pins to monitor the embankment and piezometers to measure pore water pressure</li> <li>▪ Manage the site water balance to reduce any build-up of water</li> <li>▪ Implementation of AMDMP and WMP</li> <li>▪ Geotechnical studies and assessment to ensure structural stability Engineering design to ANCOLD standard</li> <li>▪ Tracking of the waste rock and dumping locations</li> <li>▪ WRD plan</li> <li>▪ Maximisation of placement within pit</li> <li>▪ Ongoing and regular (weekly) inspections of Project areas and after rainfall events</li> <li>▪ Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc.)</li> <li>▪ Construction of Project infrastructure with suitable materials</li> <li>▪ Daily monitoring of waste rock handling and tailings disposal.</li> <li>▪ Use of a perimeter spigot with regular movement to evenly distribute tailings</li> <li>▪ Regular surveys to measure the tailings and waste rock deposition and water depths</li> <li>▪ Infrastructure design to withstand extreme events</li> <li>▪ Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc.)</li> <li>▪ Improve site drainage controls</li> <li>▪ Ongoing management of levels in water infrastructure</li> </ul>

## Section 7. Key Environmental Factors

	<ul style="list-style-type: none"> <li>▪ Environmental Management System and various management plans (EMP, WMP, MMP etc.).</li> <li>▪ All personnel will be inducted into the area and informed of the hazards and relevant management protocols of the areas</li> <li>▪ All personnel will be trained in the appropriate management practices as is relevant to their position</li> </ul> <p><b>Rehabilitation</b></p> <ul style="list-style-type: none"> <li>▪ Monitoring and active rehabilitation of disturbed soils and landscapes</li> <li>▪ Progressive clearing and rehabilitation</li> <li>▪ Revegetation of exposed areas where not proposed to be utilised</li> <li>▪ Stable design of landforms</li> <li>▪ Implementation of detailed mine closure plan</li> <li>▪ Early planning and financial provision for closure work</li> <li>▪ Review options for WRD Rehabilitation</li> <li>▪ Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>▪ Financial provisioning for closure implementation</li> <li>▪ Implement fencing and access restriction to prevent vehicle and livestock accessing rehabilitation areas</li> </ul>
<p>Groundwater drawdown from pit dewatering activities</p>	<p><b>Mitigation and Management</b></p> <ul style="list-style-type: none"> <li>▪ Groundwater monitoring</li> <li>▪ WMP</li> </ul> <p><b>Rehabilitation</b></p> <ul style="list-style-type: none"> <li>▪ Implementation of detailed mine closure plan</li> <li>▪ Early planning and financial provision for closure work</li> <li>▪ Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>▪ Financial provisioning for closure implementation</li> </ul>
<p>Groundwater interaction with site infrastructure seepage</p>	<p><b>Avoid</b></p> <ul style="list-style-type: none"> <li>▪ Design TSF to be planned, designed, constructed and operated in accordance with approaches details in the guideline Tailings Management: Leading Practice Sustainable Development Program for the Mining Industry (Australian Government 2016a).</li> <li>▪ Design TSF to contain a range of design storm and rainfall sequences events up to and greater than the required design criteria</li> <li>▪ An operational emergency spillway to be constructed as part of each embankment raise</li> <li>▪ Install seepage control and underground drainage including a cut-off trench, compact soil liner, basin underdrainage collection system, underdrain collection sump and embankment tow drain</li> <li>▪ Sump below pit decline to reclaim contaminated water</li> </ul> <p><b>Mitigation and Management</b></p> <ul style="list-style-type: none"> <li>▪ Development of Monitoring Plan / Operational Manual which includes weekly inspections of the TSF, survey pins to monitor the embankment and piezometers to measure pore water pressure</li> <li>▪ Tailings performance monitoring (e.g. TSF water volume, collection efficiency of underground system).</li> <li>▪ Groundwater monitoring to check quality and any seepage</li> <li>▪ Implementation of WMP</li> <li>▪ Manage the site water balance to reduce any build-up of water</li> <li>▪ Capping of the WRDs to reduce ongoing water infiltration and seepage</li> </ul>

## Section 7. Key Environmental Factors

	<ul style="list-style-type: none"> <li>▪ Geotechnical studies and assessment to ensure structural stability, engineering design to ANCOLD standard.</li> <li>▪ Implementation of AMDMP including ore and waste rock controls and tailings controls.</li> <li>▪ Treatment of pit and underground water to within SSTV criteria</li> <li>▪ Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc</li> <li>▪ Daily monitoring of waste rock handling and tailings disposal.</li> <li>▪ Tailings and Waste Rock will be managed in accordance with the Tailings Management Plan and Operational Manual (including inspections);</li> <li>▪ Use of a perimeter spigot with regular movement to evenly distribute tailings</li> <li>▪ Regular surveys to measure the tailings and waste rock deposition and water depths</li> <li>▪ Ongoing management of levels in water infrastructure</li> </ul> <p><b>Rehabilitation</b></p> <ul style="list-style-type: none"> <li>▪ Implementation of detailed Mine Closure Plan</li> <li>▪ Monitoring and active rehabilitation of disturbed soils and landscapes</li> <li>▪ Progressive clearing and rehabilitation</li> <li>▪ Revegetation of exposed areas where not proposed to be utilised</li> <li>▪ Stable design of landforms</li> <li>▪ Implementation of detailed mine closure plan</li> <li>▪ Early planning and financial provision for closure work</li> <li>▪ Review options for WRD Rehabilitation</li> <li>▪ Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>▪ Financial provisioning for closure implementation</li> </ul>
<p>Change in volume, spatial and temporal distribution of surface water flows</p>	<p><b>Avoid</b></p> <ul style="list-style-type: none"> <li>▪ Improve and maintain site drainage infrastructure Adherence to Ground Disturbance Procedures</li> <li>▪ Implement erosion and sediment controls in accordance with an ESCP</li> <li>▪ Only clearing what is absolutely necessary for the portion of the Project to be implemented</li> <li>▪ Clearly mark limits of clearing</li> <li>▪ Make use of already disturbed areas where possible</li> <li>▪ Avoid land clearing during the December to March portion of the wet season.</li> <li>▪ Discharge of dewatering effluent into drainage lines only during wet-season.</li> </ul> <p><b>Mitigation and Management</b></p> <ul style="list-style-type: none"> <li>▪ Implement erosion and sediment controls in accordance with an ESCP</li> <li>▪ Design TSF to contain a range of design storm and rainfall sequences events up to and greater than the required design criteria.</li> <li>▪ An operational emergency spillway to be constructed as part of each embankment raise</li> <li>▪ Install TSF seepage control and underground drainage including a cut-off trench, compact soil liner, basin underdrainage collection system, underdrain collection sump and embankment tow drain.</li> <li>▪ Tailings performance monitoring (e.g. TSF water volume, collection efficiency of underground system)</li> <li>▪ Use of a perimeter spigot with regular movement to evenly distribute tailings</li> <li>▪ Groundwater monitoring to check quality and any seepage</li> <li>▪ Implementation of AMDMP and WMP</li> <li>▪ Manage the site water balance to reduce any build-up of water</li> </ul>

## Section 7. Key Environmental Factors

	<ul style="list-style-type: none"> <li>▪ Development of Monitoring Plan / Operational Manual which includes weekly inspections of the process water dams.</li> <li>▪ Capping of the WRDs to reduce ongoing water infiltration and seepage</li> <li>▪ Regular surveys to measure the tailings and waste rock deposition and water depths</li> <li>▪ Implementation of AMD Management Plan including ore and waste rock controls and tailings controls</li> <li>▪ Treatment of pit and underground water to within SSTV criteria</li> <li>▪ Ongoing and regular (weekly) inspections of Project areas and after rainfall events</li> <li>▪ Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc.)</li> </ul> <p><b>Rehabilitation</b></p> <ul style="list-style-type: none"> <li>▪ Implementation of detailed Mine Closure Plan</li> <li>▪ Monitoring and active rehabilitation of disturbed soils and landscapes</li> <li>▪ Progressive clearing and rehabilitation</li> <li>▪ Revegetation of exposed areas where not proposed to be utilised</li> <li>▪ Stable design of landforms</li> <li>▪ Implementation of detailed mine closure plan</li> <li>▪ Early planning and financial provision for closure work</li> <li>▪ Review options for WRD Rehabilitation</li> <li>▪ Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>▪ Financial provisioning for closure implementation</li> </ul>
Flooding	<p><b>Avoid</b></p> <ul style="list-style-type: none"> <li>▪ Only clearing the practical minimum footprint necessary for the portion of the Project to be implemented</li> <li>▪ Clearly mark limits of clearing</li> <li>▪ Make use of already disturbed areas where possible</li> <li>▪ Adhere to buffer widths recommended by the Northern Territory Land Clearing Guidelines with regard to riparian vegetation in drainage lines</li> <li>▪ Avoid land clearing during the December to March portion of the wet season.</li> </ul> <p><b>Mitigation and Management</b></p> <ul style="list-style-type: none"> <li>▪ Adherence to Ground Disturbance Procedures</li> <li>▪ Design TSF to contain a range of design storm and rainfall sequence events up to and greater than the required design criteria</li> <li>▪ Manage the site water balance to reduce any build-up of water.</li> <li>▪ Development of Monitoring Plan / Operational Manual which includes weekly inspections of the process water dams.</li> <li>▪ Development of Monitoring Plan / Operational Manual which includes weekly inspections of the pits</li> <li>▪ Implementation of AMDMP and WMP</li> <li>▪ Implement drainage diversions as per the ESCP</li> <li>▪ Ongoing and regular (weekly) inspections of Project areas and after rainfall events</li> <li>▪ Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc.)</li> <li>▪ Stable design of landforms</li> </ul> <p><b>Rehabilitation</b></p> <ul style="list-style-type: none"> <li>▪ Progressive clearing and rehabilitation of disused areas</li> <li>▪ Implementation of detailed Mine Closure Plan</li> <li>▪ Monitoring and active rehabilitation of disturbed soils and landscapes</li> </ul>

## Section 7. Key Environmental Factors

	<ul style="list-style-type: none"> <li>▪ Progressive clearing and rehabilitation</li> <li>▪ Revegetation of exposed areas where not proposed to be utilised</li> <li>▪ Stable design of landforms</li> <li>▪ Implementation of detailed mine closure plan</li> <li>▪ Early planning and financial provision for closure work</li> <li>▪ Review options for WRD Rehabilitation</li> <li>▪ Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>▪ Financial provisioning for closure implementation.</li> </ul>
--	---

Due to the location of the ore bodies and constraints of the ML area available for development, it is not possible to avoid all of the minor drainage lines present in the Project area. To minimise potential impacts, the mine site design will incorporate internal stormwater drainage and water storages that will allow for capture and controlled release of excess water during the wet season. The water management arrangements (Appendix I and Appendix L) have been developed concurrently with the site-specific water balance model (Appendix H) to avoid uncontrolled discharges.

Dewatering of pits during operations will only occur during wet season when stream flows occur naturally. Discharges will be altered with existing creek flow regimes and tapering discharge volumes towards the end of the wet season, reducing potential impacts to natural flow regimes, riparian vegetation and aquatic communities. Wastewater discharges as required for operations will be undertaken in accordance with conditions of an approved WDL. In general, discharges will be controlled and timed to ensure that the volumes released do not significantly alter stream flows to a point that causes scouring or overtopping of the banks. For example, discharge from dewatering of the mining pits will occur progressively and intermittently with changing volumes. The planned dewatering activities for each individual pit are outlined in Table 7-27. Note that dewatering of the pits will be required until at least to the start date of phase 3 – post-mining. After this date the pits that have not been backfilled will be progressively flooded over time.

**Table 7-27 Overview of Pit Dewatering and Mining Phases**

	Phase 1: Pre-mining Dewatering			Phase 2: Mining	Phase 3: Post-mining	
	Start Date	End Date	Note	Start Date	Start Date	Note
Rustlers Roost pit	1/12/2021	30/04/2023	With a pause between 30/04/2022 and 1/12/2022)	1/03/2023	31/10/2031	
Annie Oakley pit	N/A	N/A	Not Applicable	1/02/2024	31/05/2024	Backfilled pit
Annie Dam pit	N/A	N/A	Not Applicable	1/03/2023	31/01/2024	Backfilled pit
Zamu pit	15/12/2024	30/04/2025	Maintain empty pit until start of operation	1/07/2025	30/06/2030	Backfilled pit
South Koolpin pit	15/02/2029	30/04/2030	Maintain empty pit until start of operation	1/07/2030	30/06/2031	
North Koolpin pit	15/02/2029	30/04/2030	Maintain empty pit until start of operation	1/07/2030	30/06/2031	
Taipan pit	15/02/2029	30/04/2030	Maintain empty pit until start of operation	1/07/2030	30/11/2031	
BHS pit	15/03/2030	30/04/2031	Maintain empty pit until start of operation	1/08/2031	30/11/2031	Backfilled pit

## Section 7. Key Environmental Factors

Sustainable levels of groundwater extraction will be determined through continued refinement of the groundwater model as further data becomes available and any measures required to protect surface and groundwater flows, will be addressed in the MMP. The proposed activities are not located within a WCD established under the *Water Act 1992*. As a result, the proposed surface water extraction from Annie's Dam and groundwater bores to supply the mine sites, does not require a licence.

### 7.3.5 Monitoring and Reporting

PGO commits to a comprehensive surface and groundwater monitoring program to improve knowledge of surface and groundwater flows and environmental water quality parameters. The monitoring program aims to detect changes in groundwater levels and monitor impacts to riparian vegetation and aquatic communities. The monitoring program will allow for adaptive management and/or rehabilitation of damage.

In summary, the following detailed monitoring and reporting measures will be included for further environmental approvals and the subsequent MMP and WMP:

- Site-specific groundwater modelling reporting including groundwater drawdown contours and assessment of potential impacts to watercourses; and
- Water Management Plan (WMP) detailing a groundwater, surface water and aquatic monitoring program and reporting, including a Trigger Action Response Plan (TARP).

The program will also include the potential area of influence to inform the requirement to assess potential cumulative impacts. Proposed monitoring sites are outlined in the WMP (Appendix I) and the WDL. In addition, water levels will be reported in accordance with any relevant legislative requirements. The appropriate monitoring and reporting framework is further outlined in more detail in Section 10.

### 7.3.6 Residual Impact

All potential residual impacts were assessed as below moderate, with the exception of impacts related to groundwater drawdown from pit dewatering activities, which are certain to occur despite the expected environmental impacts to be insignificant. Groundwater drawdown is the only source of impact that had a residual risk classified as high after the application of mitigation and management measures. Source of risk to hydrological processes associated with vegetation clearing, overtopping, embankment failure or seepage from the TSF, WRDs, process water storage, pit dewatering, erosion of site infrastructure are sources that retained a residual risk rating of moderate following application of controls.

It is acknowledged that despite the efforts to reduce the likelihood of uncontrolled discharges (i.e. from embankment failure and poor quality stormwater) the consequential impacts to surface and groundwater could still remain at a moderate level as per the definition for hydrological process impacts in the risk assessment. However, as the TSF, Process Water Dam and WRD will be planned, designed, constructed, and operated in accordance with approaches detailed in the "Leading Practice Sustainable Development Program for the Mining Industry" (Australian Government 2016a) and the relevant ANCOLD (2012) guidelines in conjunction with the development of a monitoring plan/ operational manual which includes weekly inspections of the site storage infrastructure, there is high certainty that the infrastructure embankments will remain stable.

Additionally, the potential impacts to groundwater drawdown in the vicinity of the mining pits are unavoidable. The Project will require the localised lowering of the groundwater table to maintain safe operation and mining activities. The extent of the drawdown cone has been determined by groundwater modelling undertaken during mine planning. It is not expected that there will be any impact to other consumptive users of groundwater due to their distance from the Project area. If there is a connection between the groundwater and surface water systems (which may occur in streams), drawdown could reduce

## Section 7. Key Environmental Factors

---

flows in surface water courses; however, the vegetation types present along the drainages do not indicate groundwater dependence and therefore riparian and aquatic habitats are unlikely to be affected.

Localised reduction of surface water flows will occur along short sections of streamlines located within and downstream of the Project area as a result of water being retained within the mine sites and Annie's Dam and/or associated with reduces groundwater expression into surface water courses. The reduction in flow is expected to be minor and localised due to the location in the upper catchment and therefore, relatively small contribution of the ephemeral drainage lines to downstream flows. The availability of water for use by cattle, riparian vegetation and aquatic ecosystems is unlikely to be impacted. Groundwater levels will be lowered around the pits during mining.

## Section 7. Key Environmental Factors

**Table 7-28 Hydrological Processes Residual Impact Assessment Summary**

Risk No.	Source of Impact	Project Phase(s)	Inherent Risk	Summary of Controls	Residual Risk
HP-1	Vegetation clearing for the Project	Construction Operation	Extreme	<ul style="list-style-type: none"> <li>&gt; Adherence to Ground Disturbance Procedures.</li> <li>&gt; Progressive clearing and rehabilitation.</li> <li>&gt; Implement erosion and sediment controls in accordance with an ESCP.</li> <li>&gt; Only clearing what is absolutely necessary for the portion of the Project to be implemented.</li> <li>&gt; Implementation of Biodiversity Management Plan.</li> <li>&gt; Clearly mark limits of clearing.</li> <li>&gt; Make use of already disturbed areas where possible.</li> <li>&gt; Adhere to buffer widths recommended by the Northern Territory Land Clearing Guidelines with regard to riparian vegetation in drainage lines.</li> <li>&gt; Avoid land clearing during the December to March portion of the wet season.</li> </ul>	Moderate
HP-2	Overtopping, embankment failure or seepage from the new TSF at Rustlers Roost leading to uncontrolled release of tailings material to surrounding environment.	Construction, Operation, Decommissioning or Closure	High	<ul style="list-style-type: none"> <li>&gt; TSF to be planned, designed, constructed and operated in accordance with approaches details in the guideline Tailings Management: Leading Practice Sustainable Development Program for the Mining Industry. (Australian Government 2016a).</li> <li>&gt; Design TSF to contain a range of design storm and rainfall sequences events up to and greater than the required design criteria.</li> <li>&gt; An operational emergency spillway to be constructed as part of each embankment raise.</li> <li>&gt; Development of Monitoring Plan / Operational Manual which includes weekly inspections of the TSF, survey pins to monitor the embankment and piezometers to measure pore water pressure.</li> <li>&gt; Tailings performance monitoring (e.g. TSF water volume, collection efficiency of underground system).</li> <li>&gt; Install seepage control and underground drainage including a cut-off trench, compact soil liner, basin underdrainage collection system, underdrain collection sump and embankment tow drain.</li> <li>&gt; Groundwater monitoring to check quality and any seepage.</li> <li>&gt; Implementation of AMDMP and WMP.</li> <li>&gt; Manage the site water balance to reduce any build-up of water.</li> </ul>	Moderate
HP-3	Overtopping, embankment failure or seepage from the process water storage at Rustlers Roost leading to uncontrolled	Operation, Decommissioning and Closure	High	<ul style="list-style-type: none"> <li>&gt; Development of Monitoring Plan / Operational Manual which includes weekly inspections of the process water dams.</li> </ul>	Moderate

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Inherent Risk	Summary of Controls	Residual Risk
	release of process water to surrounding environment.			<ul style="list-style-type: none"> <li>&gt; Groundwater monitoring</li> <li>&gt; Manage the site water balance to reduce any build-up of water.</li> </ul>	
HP-4	Embankment failure or seepages from the new WRDs at Rustlers Roost and Quest 29 to surrounding environment.	Operation, Decommissioning and Closure	Extreme	<ul style="list-style-type: none"> <li>&gt; Development of Monitoring Plan / Operational Manual which includes weekly inspections of the process water dams.</li> <li>&gt; Groundwater monitoring</li> <li>&gt; Manage the site water balance to reduce any build-up of water.</li> <li>&gt; Capping of the WRDs to reduce ongoing water infiltration and seepage</li> </ul>	Moderate
HP-5	Embankment failure of Annie's Dam water storage or process water ponds and uncontrolled water and sediment release.	Construction, Operation	Moderate	<ul style="list-style-type: none"> <li>&gt; Geotechnical studies and assessment to ensure structural stability</li> <li>Engineering design to ANCOLD standard.</li> <li>&gt; WMP.</li> <li>&gt; Weekly inspections to check sufficient freeboard and structural integrity.</li> </ul>	Low
HP-6	Groundwater drawdown.	Construction, Operation	High	<ul style="list-style-type: none"> <li>&gt; Hydrogeological assessment indicated that minimal connection of groundwater to Mount Bunday Creek Water MP</li> <li>&gt; No documented drawdown impacts from previous operations</li> <li>&gt; Groundwater monitoring</li> </ul>	High
HP-7	Indiscriminate use of existing waste rock for construction. Storage of waste rock outside of pit footprint for too long.	Construction Operation Decommissioning Closure	Moderate	<ul style="list-style-type: none"> <li>&gt; Tracking of the waste rock and dumping locations</li> <li>&gt; WRD plan</li> <li>&gt; ESCP to prevent mobilisation</li> <li>&gt; Maximisation of placement within pits</li> <li>&gt; On-going and regular inspections of Project areas</li> </ul>	Low
HP-8	Pit and groundwater dewatering exposing PAF and causing AMD.	Construction Operation Decommissioning Closure	High	<ul style="list-style-type: none"> <li>&gt; Sump below pit base to reclaim contaminated water</li> <li>&gt; Implementation of AMD Management Plan including ore and waste rock controls and tailings controls.</li> <li>&gt; Treatment of pit and underground water to within SSTV criteria.</li> <li>&gt;&gt; Visual inspection of pit walls to identify locations and volumes of acid producing material.</li> </ul>	Moderate
HP-9	Planned pit over topping or release to surface water features during extreme rainfall and flooding events.	Construction Operation	Low	<ul style="list-style-type: none"> <li>&gt; Development of Monitoring Plan / Operational Manual which includes weekly inspections of the pits.</li> <li>&gt; Implementation of AMDMP and WMP</li> <li>&gt; Manage the site water balance to reduce any build-up of water.</li> </ul>	Low

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Inherent Risk	Summary of Controls	Residual Risk
HP-10	Unplanned pit overtopping or release to surface water features during extreme rainfall and flooding events.	Construction Operation Decommissioning Closure	Extreme	<ul style="list-style-type: none"> <li>&gt; Development of Monitoring Plan / Operational Manual which includes weekly inspections of the pits</li> <li>&gt; Implementation of AMDMP and WMP</li> <li>&gt; Manage the site water balance to reduce any build-up of water.</li> <li>&gt; Implement drainage diversions as per the ESCP</li> </ul>	Low
HP-11	Erosion of site infrastructure leading to sedimentation	Operation, Decommissioning Closure	High	<ul style="list-style-type: none"> <li>&gt; Implementation of ESCP</li> <li>&gt; Ongoing and regular (weekly) inspections of Project areas and after rainfall events</li> <li>&gt; Avoid land clearing during wet season</li> <li>&gt; Minimise concentrated flow of surface water and ponding (drain lines, sediment bunds, liners etc.)</li> <li>&gt; Revegetation of exposed areas where not proposed to be utilised</li> <li>&gt; Stable design of landforms</li> <li>&gt; Construction of Project infrastructure with suitable materials</li> </ul>	Moderate
HP-12	Release of hazardous chemicals or materials during storage and handling onsite.	Construction, Operation, Decommissioning	Moderate	<ul style="list-style-type: none"> <li>&gt; Design, storage and handling of hazardous materials to Australian Standards and regulations.</li> <li>&gt; Specific adherence of the ANFO storage to <i>Dangerous Goods Act 1998</i> and the <i>NT Work Health and Safety (National Uniform Legislation) Act 2011</i>.</li> <li>&gt; Regular maintenance of storage facilities.</li> <li>&gt; Bunding of the process plant</li> <li>&gt; Ensure containment bunding is adequate and SDSs are available</li> <li>&gt; Diesel in bunded storage tanks, waste oil in stored bunded tanks</li> <li>&gt; Weekly inspections of storage areas, tanks, containers</li> <li>&gt; Develop Emergency Response Plan and include in inductions</li> <li>&gt; Weekly inspections of storage areas for leaks or damages</li> <li>&gt; Spill kits available around the site and procedures and training for the cleaning up of hazardous spills</li> <li>&gt; Implementation of hazardous materials management plan training for emergency response</li> <li>&gt; Cyanide management and storage will be aligned to the Commonwealth of Australia Leading Practice Handbook for Sustainable Mining - Cyanide Management (Australian Government 2008).</li> <li>&gt; Groundwater monitoring.</li> <li>&gt; Chemical storage will be located a minimum 30m from any drainage line or watercourse.</li> </ul>	Low

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Inherent Risk	Summary of Controls	Residual Risk
HP-13	Poor handling and management of tailings and waste rock	Operation, Decommissioning	Moderate	<ul style="list-style-type: none"> <li>&gt; Daily monitoring of waste rock handling and tailings disposal.</li> <li>&gt; Tailings and Waste Rock will be managed in accordance with the Tailings Management Plan and Operational Manual (including inspections).</li> <li>&gt; Use of a perimeter spigot with regular movement to evenly distribute tailings.</li> <li>&gt; Regular surveys to measure the tailings and waste rock deposition and water depths.</li> <li>&gt; Groundwater monitoring</li> </ul>	Low
HP-14	Production of domestic waste and storage of the waste onsite	Construction, Operation, Decommissioning.	Moderate	<ul style="list-style-type: none"> <li>&gt; Secure dustbin lids.</li> <li>&gt; Establish dedicated hardstand at accommodation camp for waste receptacles</li> <li>&gt; Weekly inspections of, waste area, landfill and general tidiness of site.</li> <li>&gt; Burial of waste in dedicated landfill.</li> <li>&gt; Design and construct landfill in accordance with relevant standards</li> <li>&gt; Implement leachate prevention and capture into landfill design</li> <li>&gt; Groundwater monitoring</li> <li>&gt; Segregation of wastes and recycling of wastes where possible.</li> </ul>	Low
HP-15	Unfinished/unsuccessful rehabilitation of Project due to inadequate funds or natural disaster (e.g. cyclone).	Construction, Operation, Decommissioning and Closure	Extreme	<ul style="list-style-type: none"> <li>&gt; Progressive rehabilitation of disused areas</li> <li>&gt; Implementation of detailed mine closure plan</li> <li>&gt; Early planning and financial provision for closure works</li> <li>&gt; Infrastructure design to withstand extreme events</li> <li>&gt; Ongoing management of levels in water infrastructure</li> <li>&gt; Improve site drainage controls</li> </ul>	Moderate
HP-16	Long term positive water balance	Construction, Operation, Decommissioning and Closure	High	<ul style="list-style-type: none"> <li>&gt; Improve and maintain site drainage infrastructure</li> <li>&gt; Review options for WRD Rehabilitation</li> <li>&gt; Implementation of Mine Closure Plan and adherence to commitments</li> <li>&gt; Closure Plan updated and refined throughout mining operations including LOM closure planning and contingency planning</li> <li>&gt; Financial provisioning for closure implementation</li> </ul>	Moderate
HP-17	Inappropriate management of the decommissioned site, post closure landform.	Closure	Moderate	<ul style="list-style-type: none"> <li>&gt; Implement fencing and access restriction to prevent vehicle and livestock accessing rehabilitation areas.</li> <li>&gt; Ongoing monitoring of rehabilitation.</li> <li>&gt; Progressive rehabilitation during mining to enable more established areas upon closure</li> </ul>	Low

## Section 7. Key Environmental Factors

Risk No.	Source of Impact	Project Phase(s)	Inherent Risk	Summary of Controls	Residual Risk
HP-18	Ineffective operational implementation of site environmental management system, plans and procedures.	Construction, Operation, Decommissioning Closure	High	<ul style="list-style-type: none"> <li>&gt; Corporate commitment to EMS implementation via policy</li> <li>&gt; Environmental Management System and various management plans (EMP, WMP, MMP etc.).</li> <li>&gt; All events/incidents to be reported and managed through to resolution via event/incident reporting procedures.</li> <li>&gt; All personnel will be inducted into the area and informed of the hazards and relevant management protocols of the areas.</li> <li>&gt; All personnel will be trained in the appropriate management practices as is relevant to their position.</li> </ul>	Moderate
HP-19	Inappropriate liquid and solid waste disposal.	Construction, Operation, Decommissioning Closure	High	<ul style="list-style-type: none"> <li>&gt; Manage disposal of wastes in accordance with the Project EMP (including bunded waste oil bins).</li> <li>&gt; Hazardous materials stored in accordance with Australian standards.</li> <li>&gt; Spill kits available around site and spill clean-up procedures implemented.</li> <li>&gt; Employees and contractors trained in clean up procedures.</li> <li>&gt; Weekly inspections of, waste area, landfill and general tidiness of site.</li> <li>&gt; Burial of waste in dedicated landfill.</li> <li>&gt; Design and construct landfill in accordance with relevant standards</li> <li>&gt; Implement leachate prevention and capture into landfill design</li> <li>&gt; Groundwater monitoring</li> </ul>	Low
HP-20	As part of closure and rehabilitation, creeks and drainage alignments are not consistent to the surrounding landforms and catchment area.	Closure	Moderate	<ul style="list-style-type: none"> <li>&gt; Progressively rehabilitating the mine.</li> <li>&gt; Clearing and Topsoil Procedures Implementation of Mine Closure</li> <li>&gt; Implementation of the ESCP addressing post closure drainage</li> </ul>	Low

## Section 7. Key Environmental Factors

### 7.3.7 Predicted Outcome and Conclusions

This section has outlined the risks associated with mining activities, the potential altered surface water flows and impacts to groundwater levels from alterations to creek lines and pit dewatering to the environmental vales defined for Hydrological Processes. While mining can pose risk to surface and groundwater, the risk assessment process has demonstrated that the risks can be managed in accordance with legislative requirements by relevant management plans and relevant licences.

The potential risks from uncontrolled discharge, spills and poor closure will remain throughout the Project. However, with the application of effective controls in accordance with the environmental decision framework, management and mitigation measures the risks will remain sufficiently low.

The environmental objective identified in the ToR (NT EPA 2021) is to protect hydrological processes, to support and maintain environmental values including water quality, aquatic flora and fauna and riparian vegetation. As such the Project is not determined to cause significant decline to relevant environmental, social, cultural, and economic values at the local scale.

Considering the assessment of residual impacts, and the application of mitigation and monitoring committed by PGO, it is concluded that impacts on surface and groundwater are manageable, such that the ToR objective for this factor is able to be met.

### 7.3.8 Assumptions

The key assumptions made in assessing potential impacts on hydrological processes are:

- The zone of potential impact from groundwater drawdown, while currently uncertain, is assumed to be contained mainly within the mining tenements and will not affect other users. Groundwater modelling has shown that the 1 m drawdown contours may extend 5 km to the north and 3 km to the south of the Rustlers Roost pits, and 2 km to the south-west of the Quest 29 pits;
- Due to the location at the headwaters of the catchment, any reduction in flows from altered drainage lines in ephemeral watercourses and groundwater levels will be localised and not affect the higher order watercourses downstream i.e. Mount Bunday Creek, Marrakai Creek and McKinlay River;
- Water from pit dewatering will be stored onsite in appropriate facilities during dry-season, and will only be discharged during wet-season to accommodate natural surface water flow regimes; and
- Discharge from pit watering activities into drainage and creek lines will not affect significantly natural flow patterns in higher order watercourses downstream i.e. Mount Bunday Creek, Marrakai Creek and McKinlay River.